

DAHUA

IPC-HFW1239TC1-SA-IL

Kod: 00-00005375 · Kamera



DAHUA IPC-HFW1239TC1-SA-IL-0280B 2MP 2.8MM FULL-COLOR NETWORK KAMERA

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](#)

<https://eurotechnology.az/product/dahua/ipc-hfw1239tc1-sa-il>

Texniki göstəricilər



IP

Növ



2 MP

Məqapixel



LED

İşıqlandırma



30 m

İşıqlandırma məsafəsi



Mic

Mikrofon



Sabit

Obyektiv



2.8mm

Fokus



IP67

Qoruma



Plastik

Material



MicroSD

Yaddaş



Outdoor

İş mühiti

Ətraflı məlumat

Category	Specification
Image Sensor	1/2.8" progressive CMOS, 2 MP (1920×1080)
Shutter Speed	Auto/Manual 1/3 s–1/100 000 s
Min. Illumination	0.005 lux @ F1.6 (Color, 30 IRE); 0.0005 lux (B/W); 0 lux (illuminator on)
Lens	Fixed M12 mount; 2.8 mm or 3.6 mm (F1.6)
Field of View	2.8 mm: H 104°/V 55°; 3.6 mm: H 88°/V 44°
Close Focus Distance	2.8 mm: 0.8 m; 3.6 mm: 1.3 m
Illumination Distance	IR: up to 30 m; Warm LED: up to 30 m
Smart Dual Light	Auto-switch to warm LEDs when detecting humans; reduces light pollution
Video Compression	H.265/H.264/H.264H/H.264B; Smart H.265+/H.264+; MJPEG (sub-stream)
Frame Rates	Main: 1080p @ 1–25/30 fps; Sub: 704×576/480 @ 1–25/30 fps
Image Enhancements	DWDR, 3D NR, BLC, HLC, ROI (4 areas), privacy mask (4), image rotation & mirror
Smart Detection	Human (and vehicle*) detection; motion, tampering, audio, network, IP conflict alerts
Audio	Built-in microphone; audio over IP via coax protocols
Network Features	Ethernet, PoE & 12 V DC; ONVIF support; IPv4/6; TCP/IP, RTSP, HTTP, HTTPS, DHCP, DNS, P2P, etc.
Smart Search Features	Smart NVR integration for intelligent video search/event extraction
Storage	Micro-SD slot (up to 256 GB) supported
Power & Consumption	12 V DC (±30%) or PoE (802.3af); Max ~4 W
Operating Conditions	–40 °C to +60 °C; ≤95% RH; IP67 protection
Construction & Dimensions	Metal + plastic; 180.4 × 70 × 70 mm; net weight ~0.29 kg; gross ~0.40 kg

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az