

IPC-HFW1431SP-0360B

Dahua IPC-HFW1431SP-0360B 4 MP IP kamera; Piksel 2688×1520; IR işıqlandırma - 30 m; F2.8 mm; Bucaq-104°;



Specifications

Model	IPC-HFW1431SP-0360B
Brand	Dahua
Qoruma	IP67
Növ	IP
Meqapixel	4 MP
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	3.6mm
İşıqlandırma	İR
Material	Metal
İstifadə mühiti	Outdoor

KEY FEATURES

Camera

Image Sensor 1/3" 4Megapixel progressive CMOS

Effective Pixels 2688(H)x1520(V)

RAM/ROM 512MB/32MB

Scanning System Progressive

Electronic Shutter Auto/Manual, 1/3~1/100000s

Speed

Minimum Illumination 0.08Lux/F2.0(Color,1/3s,30IRE)

0.3Lux/F2.0(Color,1/30s,30IRE)

0Lux/F2.0(IR on)

S/N Ratio More than 50dB

IR Distance Distance up to 30m(98ft)

IR On/Off Control Auto/ Manual

IR LEDs 18

Lens

Lens Type Fixed

Mount Type Board-in

Focal Length 2.8 mm (3.6 mm optional)

Max. Aperture F2.0/F2.0

Angle of View H:104°/87°, V:57°/48°

Focus Control Fixed

Close Focus Distance N/A

DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	63m(207ft)	25m(82ft)	13m(43ft)	6m(20ft)
	3.6 mm	80m(262ft)	32m(105ft)	16m(52ft)	8m(26ft)

PTZ

Pan:Tilt:0° ~360° ;Tilt:0° ~90° ;Rotation:0° ~360°

Intelligence

Event Trigger Motion detection, Video tampering, Scene changing, Network disconnection, Ip address conflict, Illegal access, Storage anomaly

IVS Tripwire, Intrusion

Video

Compression H.265/H.264H/MJPEG(Sub Stream)

Smart Codec Support H.265+/H.264+

Streaming Capability 2 Streams

Resolution 4M(2688x1520)/3M(2304x1296)/1080P(1920x1080)/720P(1280x720)/VGA(640x480)/D1(704x576/704x480)/CIF(352x288/352x240)

Frame Rate Main Stream: 4M(1 ~ 20fps)/3M (1 ~ 25/30fps)

Sub Stream: D1(1 ~ 25/30fps)

Bit Rate Control CBR/VBR

Bit Rate	H.265: 12K ~ 8448Kbps H.264: 32K ~ 10240Kbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / WDR(120dB)
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Electronic Image Stabilization (EIS)	N/A
Smart IR	Support
Digital Zoom	16x
Flip	0°/90°/180°/270°
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)
Audio	
Compression	N/A
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP;HTTPS;TCP;ARP;RTSP;RTP;RTCP;UDP;SMTP; FTP;DHCP;DNS;DDNS;PPPoE;IPV4/V6;QoS;UPnP; NTP;Bonjour;IEEE 802.1X;Multicast;ICMP;IGMP;TLS
Interoperability	ONVIF Profile S&G, API
Streaming Method	Unicast / Multicast
Max. User Access	10 Users / 20 Users
Edge Storage	NAS Local PC for instant recording
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, DSS, DMSS
Smart Phone	IOS, Android
Certifications	
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B
Interface	
Video Interface	N/A
Audio Interface	N/A
RS485	N/A
Alarm	N/A
Electrical	
Power Supply	DC12V, PoE(IEEE 802.3af)(Class 0)
Power Consumption	4.5W
Environmental	