

IPC-HFW1431T1P-ZS-S4

Dahua IPC-HFW1431T1P-ZS-S4 4 MP IP zoom kamera; Piksel 2688×1520; IR işıqlandırma - 35 m; F2.8 - 12 mm; Bucaq-98°-31°;



Specifications

Model	IPC-HFW1431T1P-ZS-S4
Brand	Dahua
Qoruma	IP67
Növ	IP
Meqapixel	4 MP
Obyektiv	Motorized
İşıqlandırma məsafəsi	30 m
Fokus	2.7 - 13.5mm
İşıqlandırma	İR
Material	Metal
İstifadə mühiti	Outdoor

KEY FEATURES

Camera

Image 1/3 "4Megapixel progressive CMOS

Sensor

Max. 2688 (H) × 1520 (V)

Resolution

ROM 128 MB

RAM 128 MB

Scanning Progressive

System

Electronic Auto/Manual 1/3 s–1/100000 s

Shutter

Speed

S/N Ratio > 56 dB

Min. 0.03 Lux @ F1.7

Illumination

Illumination 35 m (114.83 ft)

Distance

Illuminator Auto/Manual

On/Off

Control

Illuminator 2 (IR LED)

Number

Pan/Tilt/Rotation

Range Pan: 0°–360°

Tilt: 0°–90°

Rotation: 0°–360°

Pan/Tilt/Rotation Range

Lens Type Motorized vari-focal

Mount Type φ14

Focal Length 2.8 mm–12 mm

Max. F1.7

Aperture

Field of View

Horizontal: 98°–31°

Vertical: 55°–18°

Diagonal: 116°–36°

Iris Type Fixed

Close Focus 0.8 m (2.6 ft)

Distance

DORI	Lens	Detect	Observe	Recognize	Identify
------	------	--------	---------	-----------	----------

Distance

W 66.0 26.4 m 13.2 m 6.6 m
m (73.5 ft) (36.7 ft) (18.4 ft)
(183.7 ft)

T 200.0 80.0 m 40.0m 20.0 m
m (656.2 262.5 ft) (131.2 ft) (65.6 ft)

Video

Video Compression H.265; H.264; H.264B; MJPEG(only supported by sub stream)

Smart Codec Smart H.265+/ Smart H.264+

Video Frame Main Stream:

Rate 2688 × 1520 (1 fps–20 fps)
2560 × 1440 (1 fps–25/30 fps)
Sub Stream:
704 × 576 (1 fps–20/25 fps)
704 × 480 (1 fps–20/30 fps)

Stream 2 streams

Capability

Resolution 2688 × 1520 (2688 × 1520); 2560 × 1440 (2560 × 1440); 2304 × 1296 (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)

Bit Rate CBR; VBR

Control

Video Bit Rate H.264: 32 kbps–6144 kbps

Rate H.265: 12 kbps–6144 kbps

Day/Night Auto(ICR)/Color/B/W

BLC Yes

HLC Yes

WDR 120 dB

White Balance Auto/natural/street lamp/outdoor/manual/regional custom

Gain Control Manual/Auto

Noise Reduction 3D NR

Motion Detection

Motion Detection OFF/ON (4 areas, rectangular)

Region of Interest(Roi)

Region of Interest(Roi) Yes (4 areas)

Smart Illumination

Smart Illumination Yes

Image Rotation

Image Rotation 0°/90°/180°/270° (Support 90°/270° with 2688 × 1520 resolution and lower.)

Mirror Masking

Mirror Masking Yes

Privacy Masking 4 areas

Alarm

Alarm Event

Alarm Event Network disconnection; IP conflict; motion detection; video tampering; illegal access; voltage detection; security exception; defocus detection;

Network