

IPC-HFW1431T1P-ZS-S4

Dahua IPC-HFW1431T1P-ZS-S4 4 MP IP zoom kamera; Piksel 2688×1520; IR işıqlandırma - 35 m; F2.8 - 12 mm; Bucaq-98°-31°;

Model	IPC-HFW1431T1P-ZS-S4
Brend	Dahua
Qoruma	IP67
Növ	IP
Meqapixel	4 MP
Obyektiv	Motorized
İşıqlandırma məsafəsi	30 m
Fokus	2.7 - 13.5mm
İşıqlandırma	İR
Material	Metal
İş mühiti	Outdoor



Specification

Camera	
Image Sensor	1/3 "4Megapixel progressive CMOS
Max. Resolution	2688 (H) × 1520 (V)
ROM	128 MB
RAM	128 MB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s-1/100000 s
S/N Ratio	> 56 dB
Min. Illumination	0.03 Lux @ F1.7
Illumination Distance	35 m (114.83 ft)
Illuminator On/Off Control	Auto/Manual
Illuminator Number	2 (IR LED)
Pan/Tilt/Rotation Range	Pan: 0°-360° Tilt: 0°-90° Rotation: 0°-360°
Pan/Tilt/Rotation Range	
Lens Type	Motorized vari-focal
Mount Type	φ14
Focal Length	2.8 mm-12 mm
Max. Aperture	F1.7

Field of View	Horizontal: 98°-31° Vertical: 55°-18° Diagonal: 116°-36°				
Iris Type	Fixed				
Close Focus Distance	0.8 m (2.6 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	W	66.0 m (183.7 ft)	26.4 m (73.5 ft)	13.2 m (36.7 ft)	6.6 m (18.4 ft)
	T	200.0 m (656.2 ft)	80.0 m (262.5 ft)	40.0m (131.2 ft)	20.0 m (65.6 ft)
Video					
Video Compression	H.265; H.264; H.264B; MJPEG(only supported by sub stream)				
Smart Codec	Smart H.265+/ Smart H.264+				
Video Frame Rate	Main Stream: 2688 × 1520 (1 fps-20 fps) 2560 × 1440 (1 fps-25/30 fps) Sub Stream: 704 × 576 (1 fps-20/25 fps) 704 × 480 (1 fps-20/30 fps)				
Stream Capability	2 streams				
Resolution	2688 × 1520 (2688 × 1520); 2560 × 1440 (2560 × 1440); 2304 × 1296 (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)				
Bit Rate Control	CBR; VBR				
Video Bit Rate	H.264: 32 kbps-6144 kbps H.265: 12 kbps-6144 kbps				
Day/Night	Auto(ICR)/Color/B/W				
BLC	Yes				
HLC	Yes				
WDR	120 dB				
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom				
Gain Control	Manual/Auto				
Noise Reduction	3D NR				
Motion Detection	OFF/ON (4 areas, rectangular)				
Region of Interest(RoI)	Yes (4 areas)				
Smart Illumination	Yes				
Image Rotation	0°/90°/180°/270° (Support 90°/270° with 2688 × 1520 resolution and lower.)				
Mirror	Yes				
Privacy Masking	4 areas				
Alarm					
Alarm Event	Network disconnection; IP conflict; motion detection; video tampering; illegal access; voltage detection; security exception; defocus detection;				
Network					
Network	RJ-45 (10/100 Base-T)				
SDK and API	Yes				
Cyber Security	Video encryption; firmware encryption; configuration encryption; Digest; WSSE; account lockout; security logs; IP/MAC filtering; generation and importing of X.509 certification; syslog; HTTPS; 802.1x; trusted boot; trusted execution; trusted upgrade				
Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; Bonjour				
Interoperability	ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; Genetec; P2P				
User/Host	20				
Storage	FTP; SFTP; Micro SD card (support max. 256 GB); NAS				

Browser	IE Chrome Firefox
Management Software	Smart PSS; DSS; DMSS
Mobile Phone	IOS; Android
Certification	
Certifications	CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B
Power	
Power Supply	12V DC/POE (802.3af)
Power Consumption	< 7.5W (PoE)
Environment	
Operating Conditions	-30°C to +55°C (-22°F to +131°F) /less than95%
Storage Conditions	-40°C to +60°C (-40°F to +140°F)
Protection	IP67
Structure	
Casing	Metal + plastic
Dimensions	243.5 mm x Ø90.7 mm (9.6" x Ø3.6")
Net Weight	0.44 kg (1.0 lb)
Gross Weight	0.69 kg (1.5 lb)