

IPC-HFW2231T-ZS-S2

Dahua IPC-HFW2231T-ZS-S2 2 MP IP zoom kamera; Piksel 1920×1080; IR işıqlandırma - 60 m; F2.7–13.5mm; Bucaq-108°–30°;

Model	IPC-HFW2231T-ZS-S2
Brend	Dahua
Qoruma	IP67
Növ	IP
Meqapixel	2 MP
Obyektiv	Motorized
Fokus	2.7 - 13.5mm
İşıqlandırma	İR
İşıqlandırma məsafəsi	60 m
Material	Metal
İş mühiti	Outdoor



Specification

Camera	
Image Sensor	1/2.8" CMOS
Max. Resolution	1920 (H) × 1080 (V)
ROM	128 MB
RAM	128 MB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Min. Illumination	0.002 Lux@F1.6 (Color, 30 IRE) 0.0002 Lux@F1.6 (B/W, 30 IRE) 0 Lux (Illuminator on)
S/N Ratio	> 56 dB
Illumination Distance	60 m (196.85 ft) (IR)
Illuminator On/Off Control	Auto; manual
Illuminator Number	4 (IR LED)
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°
Lens	
Lens Type	Motorized vari-focal
Lens Mount	φ14
Focal Length	2.7mm–13.5mm
Max. Aperture	F1.5
Field of View	Horizontal: 108°–30° Vertical: 56°–17° Diagonal: 131°–35°

Iris Control	Fixed				
Close Focus Distance	0.8 m (2.62 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	W	44.1 m (144.69 ft)	17.7 m (58.07 ft)	8.8 m (28.87 ft)	4.4 m (14.44 ft)
	T	144.8 m (475.07 ft)	57.9 m (189.96 ft)	29.0 m (95.14 ft)	14.5 m (47.57 ft)
Smart Event					
IVS	Tripwire; intrusion				
Video					
Video Compression	H.265; H.264; H.264B; MJPEG (Only supported by the sub stream)				
Smart Codec	Smart H.265+; Smart H.264+				
Video Frame Rate	Main stream: 1920 x 1080@1-25/30 fps Sub stream: 704 x 576@1-25 fps 704 x 480@1-30 fps *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.				
Stream Capability	2 streams				
Resolution	1080p (1920 x 1080); 1.3M (1280 x 960); 720p (1280 x 720); D1 (704 x 576/704 x 480); VGA (640 x 480); CIF (352 x 288/352 x 240)				
Bit Rate Control	CBR/VBR				
Video Bit Rate	H.264: 32 kbps-6144 kbps H.265: 12 kbps-6144 kbps				
Day/Night	Auto (ICR)/Color/B/W				
BLC	Yes				
HLC	Yes				
WDR	120 dB				
White Balance	Auto; natural; street lamp; outdoor; manual; regional custom				
Gain Control	Auto; manual				
Noise Reduction	3D NR				
Motion Detection	OFF/ON (4 areas, rectangular)				
Region of Interest (RoI)	Yes (4 areas)				
Smart Illumination	Yes				
Image Rotation	0°/90°/180°/270° (Support 90°/270° with 1080p resolution and lower)				
Mirror	Yes				
Privacy Masking	4 areas				
Alarm					
Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; defocus detection; tripwire; intrusion; voltage detection; security exception				
Network					
Network Port	RJ-45 (10/100 Base-T)				
SDK and API	Yes				
Cyber Security	Video encryption; firmware encryption; configuration encryption; Digest; WSSE; account lockout; security logs; IP/MAC filtering; generation and importing of X.509 certification; syslog; HTTPS; 802.1x; trusted boot; trusted execution; trusted upgrade				
Network Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; Bonjour				
Interoperability	ONVIF (Profile S/Profile G/Profile T); CGI; P2P; Milestone				
User/Host	20 (Total bandwidth: 48 M)				
Storage	FTP; SFTP; Micro SD card (support max. 256 G); NAS				
Browser	IE Chrome Firefox				
Management Software	Smart PSS; DSS; DMSS				
Mobile Client	IOS; Android				

Certification	
Certifications	CE-LVD: EN 62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
Power	
Power Supply	12 V DC/PoE
Power Consumption	Basic: 1.8 W (12 V DC); 2.2 W (PoE) Max. (ICR + H.265 + max. resolution + main stream + IR intensity + WDR + IVS + vari-focal); 8.2 W (12 V DC); 9.8 W (PoE)
Environment	
Operating Temperature	-30 °C to +60 °C (-22 °F to +140 °F)
Operating Humidity	≤ 95%
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Protection	IP67; IK10 (optional)
Structure	
Casing	Metal
Product Dimensions	244.1 mm × Ø90.4 mm (9.6" × Ø3.6")
Net Weight	0.89 kg (2.0 lb)
Gross Weight	1.13 kg (2.5 lb)