

IPC-HFW2431TP-AS-0360B-S2

Dahua IPC-HFW2431TP-AS-0360B-S2 4 MP səsli IP kamera; Piksel 2688×1520; IR işıqlandırma - 30 m; F3.6 mm; Bucaq-87°; Audio(Mikrofon)



Specifications

Model	IPC-HFW2431TP-AS-0360B-S2
Brand	Dahua
Çalışma mühiti	Outdoor
Növ	IP
Meqapixel	4 MP
İşıqlandırma məsafəsi	80 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	3.6mm
İşıqlandırma	İR
Qoruma	IP67
Material	Metal

KEY FEATURES**Camera****Image** 1/3" 4Megapixel progressive CMOS**Sensor****Max.** 2688 (H) × 1520 (V)**Resolution****ROM** 128 MB**RAM** 128 MB**Scanning** Progressive**System****Electronic** Auto/Manual 1/3 s–1/100,000 s**Shutter****Speed****Min.** 0.008 Lux@F1.6**Illumination****S/N Ratio** > 56 dB**Illumination** 80 m (262.5 ft)**Distance****Illuminator** Auto/Manual**On/Off****Control****Illuminator** 4 (IR LED)**Number****Pan/Tilt/Rotation****Range** Pan: 0°–360°

Tilt: 0°–90°

Rotation: 0°–360°

Lens**Lens Type** Fixed-focal**Mount Type** M12**Focal Length** 3.6 mm; 6 mm; 8 mm**Max.****Aperture** 3.6 mm: F1.6

6 mm: F1.6

8 mm: F1.6

Field of View

3.6 mm: Horizontal 84° × Vertical 45° × Diagonal 100°

6 mm: Horizontal 52° × Vertical 28° × Diagonal 61°

8 mm: Horizontal 40° × Vertical 23° × Diagonal 45°

Iris Type

Fixed

Close Focus
Distance 3.6 mm: 1.4 m (4.6 ft)
 6 mm: 3.1 m (10.2 ft)
 8 mm:4.9 m(16.1 ft)

DORI	Lens	Detect	Observe	Recognize	Identify
Distance	3.6 mm	80 m (262.5 ft)	32.0 m (105.0 ft)	16.0 m (52.5 ft)	8.0 m (26.2 ft)
	6 mm	120.0 m (393.7 ft)	48.0 m (157.5 ft)	24.0 m (78.7 ft)	12.0 m (39.4 ft)
	8 mm	160.0 m (524.9 ft)	64.0 m (210.0 ft)	32.0 m (105.0 ft)	16.0m (52.5 ft)

Smart Event
IVS Tripwire; intrusion
Video
Video
Compression H.265; H.264; H.264B; MJPEG(only supported by the sub stream)

Smart Codec Smart H.265+/ Smart H.264+

Video Frame
Rate Main stream:
 2688 × 1520 (1 fps–20 fps)
 2560 × 1440 (1 fps–25/30 fps)
 Sub stream:
 704 × 576 (1 fps–25 fps)
 704 × 480 (1 fps–30 fps)

Stream 2 streams
Capability
Resolution 2688 × 1520 (2688 × 1520); 2560 × 1440 (2560 × 1440); 3M (2048 × 1536); 2304 × 1296 (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)

Bit Rate CBR/VBR
Control
Video Bit
Rate H.264: 32 kbps–6144 kbps
 H.265: 12 kbps–6144 kbps

Day/Night Auto(ICR)/Color/B/W
BLC Yes
HLC Yes
WDR 120 dB
White Auto/natural/street lamp/outdoor/manual/regional custom
Balance
Gain Control Auto/Manual
Noise 3D NR
Reduction
Motion OFF/ON (4 areas, rectangular)
Detection

Region of Yes (4 areas)
Interest (RoI)