

IPC-HFW2449SP-S-IL-0280B

Dahua IPC-HFW2449SP-S-IL-0280B 4 MP IP Full color (rəngli) səsli WizSense kamera; Piksel 2688×1520; IR işıqlandırma - 30 m; F2.8 mm; Bucaq-95°;Audio(mikrofon)



Specifications

Model	IPC-HFW2449SP-S-IL-0280B
Brand	Dahua
?? mühiti	Outdoor
Növ	IP
Meqapixel	4 MP
???qland?rma	LED
???qland?rma m?saf?si	30 m
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Metal

KEY FEATURES

Camera

Image Sensor 1/2.9" CMOS

Max. 2688 (H) × 1520 (V)

Resolution

ROM 128 MB

RAM 128 MB

Scanning Progressive

System

Electronic Auto/Manual 1/3 s–1/100,000 s

Shutter Speed

Min. 0.006 lux@F1.6 (Color, 30 IRE)

Illumination 0.0006 lux@F1.6 (B/W, 30 IRE)
0 lux (Illuminator on)

S/N Ratio >56 dB

Illumination 30 m (98.43 ft) (IR), 30 m (98.43 ft) (Warm light)

Distance

Illuminator Auto;Manual

On/Off Control

Illuminator 1 (IR LED); 1 (Warm light)

Number

Pan/Tilt/Rotation Pan: 0°–360°

Range Tilt: 0°–90°
Rotation: 0°–360°

Lens

Lens Type Fixed-focal

Lens Mount M12

Focal Length 2.8 mm; 3.6 mm

Max. Aperture F1.6

Field of View 2.8 mm: H: 95°; V: 52°; D: 114°;
3.6 mm: H: 78°; V: 41°; D: 94°

Iris Control Fixed

Close Focus

Distance 2.8 mm: 0.9 m (2.95 ft);
3.6 mm: 1.6 m (5.25 ft)

DORI Distance Lens	Detect	Observe	Recognize	Identify
2.8 mm	63.6 m (208.66 ft)	25.4 m (83.33 ft)	12.7 m (41.67 ft)	6.4 m (20.99 ft)
3.6 mm	85.4 m (280.18 ft)	34.2 m (112.20 ft)	17.1 m (56.10 ft)	8.5 m (27.89 ft)

Intelligence

IVS (PerimeterIntrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human Protection)	
Smart Search Video	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos
Video Compression	H.264H; H.265; H.264; H.264B; MJPEG (Only supported by the sub stream)
Smart Codec	Smart H.265+; Smart H.264+
Video Frame Rate	Main stream: 2688 × 1520@(1-20 fps)/2566 × 1440@(1-25/30 fps) Sub stream: 704 × 576@(1-25 fps)/704 × 480@(1-30 fps) *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Stream Capability	2 streams
Resolution	4M (2688 × 1520); 3.6M (2560 × 1440); 3M (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
Bit Rate Control	CBR/VBR
Video Bit Rate	H.264: 32 kbps-6144 kbps; H.265: 12 kbps-6144 kbps
Day/Night	Auto (ICR)/Color/B/W
BLC	Yes
HLC	Yes
WDR	120 dB
White Balance	Auto; natural; street lamp; outdoor; manual; regional custom
Gain Control	Auto;Manual
Noise Reduction	3D NR
Motion Detection	OFF/ON (4 areas, rectangular)
Region of Interest (RoI)	Yes (4 areas)
Smart Illumination	Yes
Image Rotation	0°/90°/180°/270° (Support 90°/270° with 2688 × 1560 resolution and lower)
Mirror	Yes
Privacy Masking	4 areas
Audio	
Built-in MIC	Yes
Audio Compression	G.711a; G.711Mu; PCM; G.726
Alarm	
Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion detection; video tampering; tripwire; intrusion; SMD; voltage detection; security exception
Network	
Network Port	RJ-45 (10/100 Base-T)
SDK and API	Yes
Network Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP