

# IPC-HFW3249EP-AS-LED

DAHUA - IPC-HFW3249EP-AS-LED 2MP FULL-COLOR WIZESENSE NETWORK KAMERA, LED işıqlandırma, IR 50m məsafə və AI dəstəyi ilə yüksək dəqiqlikdə görüntü təqdim edir. Səsli nəzarət üçün daxili mikrofon, H.265+ sıxılma, WDR və PoE dəstəyi ilə həm gündüz, həm də gecə ideal müşahidə imkanı yaradır.



## Specifications

Model	IPC-HFW3249EP-AS-LED
Brand	Dahua
Növ	IP
Meqapixel	2 MP
İşıqlandırma	LED
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma məsafəsi	30 m
Mikrofon	Mic
Qoruma	IP67
Material	Metal
Yaddaş	MicroSD
İstifadə mühiti	Outdoor

## KEY FEATURES

## Camera

Image Sensor 1/2.8"2Megapixel progressive CMOS

Max. Resolution 1920 (H) × 1080 (V)

ROM 128 MB

RAM 512 MB

Scanning System Progressive

Electronic Shutter Auto/Manual 1/3 s–1/100,000 s

Speed

Min. Illumination 0.0015 Lux@F1.0

S/N Ratio &gt;56 dB

Illumination Distance 30 m (98.4 ft)

Illuminator On/Off Control Auto/Manual

Illuminator Number 1 (warm LED)

Pan/Tilt/Rotation Range Pan: 0°–360°; Tilt: 0°–90°; Rotation: 0°–360°

## Lens

Lens Type Fixed-focal

Lens Mount M12

Focal Length 2.8 mm; 3.6 mm

Max. Aperture F1.0

Field of View 2.8 mm: Horizontal:107°; vertical: 55°; diagonal: 127°  
3.6 mm: Horizontal:84°; vertical: 45°; diagonal: 99°

Iris Control Fixed

Close Focus Distance 2.8 mm: 0.8 m (2.6 ft)

3.6 mm: 1.7 m (5.6 ft)

DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	38.6 m (126.6 ft)	15.4 m (50.5 ft)	7.7 m (25.3 ft)	3.9 m (12.8 ft)
	3.6 mm	55.2 m (181.1 ft)	22.1 m (72.5 ft)	11.0 m (36.1 ft)	5.5 m (18.0 ft)

## Intelligence

IVS (Perimeter Protection) Tripwire, intrusion (support the classification and accurate detection of vehicle and human)

Smart Search Video Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos

Video Compression H.265; H.264; H.264H; H.264B; MJPEG (only supported by the sub stream)

Smart Codec Smart H.265+  
Smart H.264+

<b>Video Frame Rate</b>	<p>Main stream (1920 × 1080 @ 1–25/30 fps)</p> <p>sub stream (704 × 576 @ 1–25/704 × 480 @ 1-30 fps)</p> <p>third stream (1280 × 720 @ 1–25/30 fps)</p>
<b>Stream Capability</b>	3 streams
<b>Resolution</b>	1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
<b>Bit Rate Control</b>	CBR/VBR
<b>Video Bit Rate</b>	H.264: 3 kbps–8192 kbps H.265: 3 kbps–8192 kbps
<b>Day/Night</b>	Color/B/W
<b>BLC</b>	Yes
<b>WDR</b>	120 dB
<b>Scene Self-adaptation (SSA)</b>	Yes
<b>White Balance</b>	Auto; natural; street lamp; outdoor; manual; regional custom
<b>Gain Control</b>	Auto/Manual
<b>Noise Reduction</b>	3D NR
<b>Motion Detection</b>	OFF/ON (4 areas, rectangular)
<b>Region of Interest (RoI)</b>	Yes (4 areas)
<b>Smart Illumination</b>	Yes
<b>Image Rotation</b>	0°/90°/180°/270° (support 90°/270° with 1920 × 1080 resolution and lower)
<b>Mirror</b>	Yes
<b>Privacy Masking</b>	4 areas
<b>Audio</b>	
<b>Built-in MIC</b>	Yes
<b>Audio Compression</b>	G.711a; G.711Mu; G726
<b>Alarm</b>	
<b>Alarm Event</b>	<p>No SD card; SD card full; SD card error; less service time of SD card (smart card supports); network disconnection; IP conflict;</p> <p>illegal access; voltage detection; security exception; motion detection; video tampering; scene changing;</p> <p>input abnormal; intensity change; tripwire; intrusion; SMD</p>
<b>Network</b>	
<b>Network Port</b>	RJ-45 (10/100 Base-T)
<b>SDK and API</b>	Yes
<b>Network Protocol</b>	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; SNMP
<b>Cyber Security</b>	<p>Video encryption; Firmware encryption; Configuration encryption; Digest; WSSE; Account lockout; Security logs; IP/MAC filtering;</p> <p>Generation and importing of X.509 certification; syslog; HTTPS; 802.1x; Trusted boot; Trusted execution; Trusted upgrade</p>
<b>Interoperability</b>	ONVIF (Profile S/Profile G/Profile T); CGI; P2P; Milestone; Genetec