

IPC-HUM4231SP-L4-0280B-S3

IPC-HUM4231SP-L4-0280B-S3



Specifications

Model	IPC-HUM4231SP-L4-0280B-S3
Brand	Dahua
?? mühiti	Indoor
Növ	IP
Meqapixel	2 MP
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
???qland?rma	IR
???qland?rma m?saf?si	20 m
Qoruma	IP67
Material	Metal

KEY FEATURES

Model IPC-HUM4231SP-L4-0280B-S3

Camera

Matrix 1/3" CMOS

Effective pixels 1920×1080

ROM 128 MB

RAM 128 MB

Scanning system Progressive

Electronic shutter speed Auto / Manual 1 / 3 s – 1 / 100,000 s

Min. lighting 0.01 Lux at F2.0 (Color, 30 IRE)
0.001 Lux at F2.0 (B/W, 30 IRE)

Signal/Noise Ratio >56 dB

Lens

Lens type Fixed

Mounting type M12

Focal length 2.8 mm

Max. diaphragm F2.0

Viewing angle Horizontal:96°; Vertical:55°; Diagonal:110°

IR control Fixed

Closed focal length 0.8 m (2.62 ft)

DOOR	Lens	Detection	Notification	Recognition	Identification
Distance	2.8 mm	61.0 m (200.13 ft)	24.4 m (80.05 ft)	12.2 m (40.03 ft)	6.4 m (20.01 ft)

Smart events

IVS Tripwire/Invasion

Video

Video compression N.265; H.264; N.264B; MJPEG (Only supported by additional stream)

Smart Codec Smart H.265+; Smart H.264+

Video frame rate Main stream: 1920 × 1080 @ (1-25/30 fps)
Sub. Stream: 704 × 576 (1-25 fps) / 704 × 480 (1-30 fps)

* The above values are the maximum frame rates of each stream; for multiple streams, the values will depend on the total encoding capacity.

Streaming Features 2 streams

Permission	1080p (1920 × 1080); 1.3M (1920 × 960); 720p (1280 × 720); D1 (704 × 576 / 704 × 480); VGA (640 × 480); CIF(352 × 288 / 352 × 240)
Data transfer rate control	CBR/VBR
Video bit rate	H.264:3 kbps–6144 kbps H.265:3 kbps–6144 kbps
Day Night	Color/B/W
BLC	Eat
HLC	Eat
WDR	120 dB
White Balance	Auto / Natural light / Street lamp / Outdoor / Manual / Regular
Gain control	Auto / Manual
Noise suppression	3D NR
Motion Detection	Off / On (4 Zones, Rectangle)
Area of Interest (RoI)	Yes (4 Zones)
Frame rotation	0° / 90° / 180° / 270° (Support 90° / 270° with 1080P resolution and below)
Display	Eat
Privacy mask	4 zones
Audio	
Built-in microphone	Eat
Audio compression	G.711a; G.711Mu; PCM; G.726
Anxiety	
Alarming events	Network shutdown; IP conflict; Illegal access; Motion Detection; Video violation; Stretching; Invasion; Sound detection; Voltage detection; Security Exception
Net	
Network port	RJ-45 (10/100 Base-T)
SDK and API	Eat
Cyber security	Video encryption; Firmware encryption; Configuration encryption; Digest; WSSE; Account blocking; Security logs; IP/MAC filtering; Generate and import X.509 certificate; System log; HTTPS; 802.1x; Trusted download; Entrusted execution; Reliable update
Network protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; Bonjour
Compatibility	ONVIF (Profile S / Profile T); CGI; P2P; Milestone
User/Host	20 (Total bandwidth: 48 MB)
Storage	FTP; SFTP; NAS
Browser	IE Chrome Firefox
Management software	Smart PSS; DSS; DMSS
Smartphones	iOS; Android

Ports

Audio Input 1 channel (RCA port)