

# IPC2122LB-ADF28KM-G

IPC2122LB-ADF28KM-G 2MP 2.8MM IR 30M 2MP WDR Fixed IR Bullet Network Kamera UNV



## Specifications

Model	IPC2122LB-ADF28KM-G
Brand	Uniview
Növ	IP
Meqapixel	2 MP
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
???qland?rma	İR
???qland?rma m?saf?si	30 m
Qoruma	IP67
Material	Metal
Yadda?	MicroSD
?? mühiti	Outdoor

KEY FEATURES

IPC2122LB-ADF28KM-G

IPC2122LB-ADF40KM-G

Camera

Sensor 1/2.7", 2.0 megapixel, progressive scan, CMOS

Minimum Illumination Colour: 0.01Lux ( F2.0, AGC ON)

0Lux with IR

Day/Night IR-cut filter with auto switch (ICR)

Shutter Auto/Manual, 1 ~ 1/100000s

Adjustment Angle Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°

S/N >52dB

WDR 120dB

Lens

Lens Type 2.8mm and 4.0mm @2.0, Fixed-focal

Lens Mount M12

Angle of View (H) 112.9° 91.2°

Angle of View (V) 59.1° 47.9°

Angle of View (O) 121.2° 95.9°

DORI

DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	42.0	16.8	8.4	4.2
	4.0	60.0	24.0	12.0	6.0

Illuminator

IR Range Up to 30m (98ft) IR range

Wavelength 850nm

IR On/Off Control Auto/Manual

Video

Video Ultra 265, H.265, H.264, MJPEG

Compression

H.264 code profile Baseline profile, Main profile, High profile

Frame Rate Main Stream: 1080P (1920\*1080), Max 30fps; 720P (1280\*720), Max 30fps  
Sub Stream: 720P (1280\*720), Max 30fps; D1 (720\*576), Max 30fps; 640\*360, Max 30fps; 2CIF(704\*288), Max 30fps;  
CIF(352\*288), Max 30fps;

Video Bit Rate 128 Kbps~6144 kbps

U-code Supported

9:16 Corridor Supported

Mode

OSD Up to 4 OSDs

Privacy Mask Up to 4 areas

ROI Up to 8 areas

Motion Detection Up to 4 areas

Image

<b>White Balance</b>	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
<b>Image Setting</b>	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser
<b>Digital Noise Reduction</b>	2D/3D DNR
<b>Smart IR</b>	Supported
<b>Flip</b>	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise
<b>Dewarping</b>	N/A
<b>HLC</b>	Supported
<b>BLC</b>	Supported
<b>Defog</b>	Digital Defog
<b>Audio</b>	
<b>Audio</b>	G.711
<b>Compression</b>	
<b>Suppression</b>	Supported
<b>Sampling Rate</b>	8KHZ
<b>Storage</b>	
<b>Edge Storage</b>	Micro SD, up to 128GB
<b>Network Storage</b>	ANR,NAS(NFS)
<b>Network</b>	
<b>Protocols</b>	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP
<b>Compatible Integration</b>	ONVIF (Profile S, Profile G, Profile T), API , SDK
<b>User/Host</b>	Up to 32 users. 2 user levels: administrator and common user
<b>Security</b>	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
<b>Client</b>	EZStation EZView EZLive
<b>Web Browser</b>	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+
<b>Interface</b>	
<b>Network</b>	1 * RJ45 10M/100M Base-TX Ethernet
<b>Built-in Mic</b>	Supported
<b>Certifications</b>	
<b>EMC</b>	FCC: FCC Part 15
<b>Safety</b>	CE: EN 60950-1 UL: UL60950-1 IEC 60950-1
<b>General</b>	
<b>Power</b>	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 7.0W
<b>Power Interface</b>	Ø 5.5mm coaxial power plug
<b>Dimensions (L × W × H)</b>	165 × 63 × 62mm (6.5" × 2.5" × 2.5")
<b>Weight</b>	0.39kg (0.86lb)
<b>Material</b>	Metal + plastic
<b>Working Environment</b>	-30°C ~ 60°C (-22°F ~ 140°F) Humidity: ≤95% RH (non-condensing)
<b>Storage</b>	-30°C ~ 60°C (-22°F ~ 140°F) Humidity: ≤95% RH (non-condensing)