

IPC2122LB-ASF28K-A

IP CAM UNIVIEW IPC2122LB-ASF28K-A, 2MP, 2.8mm, 30m, Audio (Mikrofon), IP67



Specifications

Model	IPC2122LB-ASF28K-A
Brand	Uniview
Növ	IP
Meqapixel	2 MP
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
??qland?rma	İR
??qland?rma m?saf?si	30 m
Qoruma	IP67
Material	Plastik
Yadda?	MicroSD
?? mühiti	Outdoor

KEY FEATURES

IPC2122LB-ASF28K-A

Camera

Max Resolution	2MP
Sensor	1/2.9" CMOS
Min. Illumination	Colour:0.01 lux (F2.0, AGC ON) 0 lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
Shutter	Auto/Manual, 1 ~ 1/100000s
Adjustment Angle	Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotate: 0° ~ 360°

S/N >52dB

WDR DWDR

Lens

Focal Length 2.8 mm

Iris Type Fixed

Iris F2.0

Field of View (H) 101.1°

Field of View (V) 56.5°

Field of View (D) 117°

DORI

DORI Distance 2.8mm

(Lens)

DORI Distance 45.0m(147.6ft)

(Detect)

DORI Distance 18.0m(59.1ft)

(Observe)

DORI Distance 9.0m(29.5ft)

(Recognize)

DORI Distance 4.5m(14.8ft)

(Identify)

Illuminator

Supplemental Light IR

Illumination 30 m (98.4 ft)

Distance (IR)

Wavelength 850 nm

IR On/Off Control Auto/Manual

Video

Video Compression Ultra 265, H.265, H.264

H.264 Code Profile Baseline profile, Main profile, High profile

Frame Rate Main Stream: 2MP (1920*1080),Max 30fps; 720P (1280*720),Max 30fps
Sub Stream: D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps

Video Bit Rate 128 Kbps ~ 6144 Kbps

U-code Support (Main stream)

OSD Up to 4 OSDs

Privacy Mask	Up to 4 areas
ROI	Support
Video Stream	Dual Streams
Image	
White Balance	Auto, Outdoor, Fine Tune, Sodium Lamp, Locked, Auto2
Digital Noise Reduction	2D/3D DNR
Smart IR	Support
Flip	Normal, Flip Vertical, Flip Horizontal, 180°
Dewarping	N/A
HLC	Support
BLC	Support
Defog	Digital Defog
Events	
Basic Detection	Motion Detection, Audio Detection
General Function	Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication, HTTP Authentication
Audio	
Audio Compression	G.711U/G.711A
Audio Bitrate	64 Kbps
Two-way Audio	N/A
Suppression	Support
Sampling Rate	8 KHz
Storage	
Edge Storage	Micro SD, up to 512 GB
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, UPnP, HTTP, HTTPS, QoS, SSL/TLS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
User/Host	Up to 32 users, 2 user levels: administrator and common user
Security	Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, WSSE and Digest Authentication for ONVIF
Client	UNV-Link, UNV-Link Pro, EZStation
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above, Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above
Interface	
Audio I/O	N/A
Alarm I/O	N/A
Serial Port	N/A
Built-in Mic	Support
Built-in Speaker	N/A
WIFI	N/A
Network	1 x RJ45 10M/100M Base-TX Ethernet
Video Output	N/A
Certification	
EMC	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035) FCC (FCC 47 CFR part15 B)
Safety	CE LVD (EN 62368-1) © 2026 Uniview. All rights reserved. Eurotechnology CB (IEC 62368-1)