

IPC2122LE-ADF40KMC-WL

IPC2122LE-ADF40KMC-WL 2MP 4MM IR 30M HD ColorHunter Mini IR Fixed Bullet Network Kamera UNV



Specifications

Model	IPC2122LE-ADF40KMC-WL
Brand	Uniview
Növ	IP
Meqapixel	2 MP
??qland?rma	LED
??qland?rma m?saf?si	30 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	4mm
Qoruma	IP67
Material	Metal
Yadda?	MicroSD
?? mühiti	Outdoor

KEY FEATURES

	IPC2122LE-ADF28KMC-WL	IPC2122LE-ADF40KMC-WL
Camera		
Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS	
Minimum Illumination	Colour: 0.003 lux (F1.6, AGC ON) 0Lux with light	
Day/Night	IR-cut filter with auto switch (ICR)	
Shutter	Auto/Manual, 1 ~ 1/100000s	
Adjustment Angle	Pan: 0° ~ 360° Tilt: 0° ~ 90°	Rotate: 0° ~ 360°
S/N	>52dB	
WDR	120dB	
Lens		
Lens Type	2.8mm @F1.6	4.0mm @F1.6
Iris	Fixed	
Field of View (H)	106.7°	87.5°
Field of View (V)	57.1°	46.3°
Field of View (D)	115.7°	92.4°
DORI		
DORI Distance	Lens (mm) Detect (m) Observe (m) Recognize (m) Identify (m)	
	2.8 43.4 17.4 8.7 4.3	
	4.0 62.1 24.8 12.4 6.2	
Illuminator		
IR Range	Up to 30m (98ft) IR range	
White Light Range	Up to 30m (98ft) white light range	
Wavelength	850nm	
IR On/Off Control	Auto/Manual	
Video		
Video	Ultra 265, H.265, H.264, MJPEG	
Compression		
H.264 Code Profile	Baseline profile, Main profile, High profile	
Frame Rate	Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;	
Video Bit Rate	128 Kbps~6 Mbps	
U-code	Support	
OSD	Up to 4 OSDs	
Privacy Mask	Up to 4 areas	
ROI	Up to 8 areas	
Video stream	Dual streams	
Image		
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2	
Digital Noise Reduction	2D/3D DNR	
Smart IR	Supported	

Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise
HLC	Supported
BLC	Supported
Defog	Digital Defog
Events	
Basic Detection	Cross line, intrusion(based on human body detection),motion detection, tampering alarm, audio detection
General Function	Watermark, IP address filtering, access policy, ARP protection, RTSP authentication, user authentication, HTTP authentication
Audio	
Audio	G.711A/G.711U
Compression	
Audio Bitrate	64 Kbps
Two-way Audio	Support
Suppression	Support
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, up to 128GB
Network Storage	ANR, NAS(NFS)
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, SNMP
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API , SDK
User/Host	Up to 32 users. 2 user levels: administrator and common user
Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Client	EZStation EZView EZLive
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above
Interface	
Audio I/O	N/A
Alarm I/O	N/A
RS485	N/A
Built-in Mic	Support
Built-in Speaker	Support
WIFI	N/A
Network	1 * RJ45 10M/100M Base-TX Ethernet
Video Output	N/A
Certification	
EMC	CE-EMC (EN 55032: 2015+A1:2020,EN 61000-3-3: 2013+A1: 2019,EN IEC 61000-3-2: 2019+A1: 2021,EN 55035: 2017+A11:2020) FCC (FCC CFR 47 part15 B, ANSI C63.4-2014)
Safety	CE LVD (EN 62368-1:2014+A11:2017) CB (IEC 62368-1:2014) UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)
Protection	IP67 (IEC 60529:1989+AMD1:1999+AMD2:2013)
General	© 2026 Uniview. All rights reserved. Eurotechnology
Power	DC 12V±25%, PoE (IEEE 802.3af)