

IPC2312LE-ADF28KM-WP

IPC2312LEADF28KM-WP 2MP 2.8mm COLORHUNTER Wise-ISP FIXED WARM LIGHT BULLET NETWORK KAMERA UNV

| | |
|-----------------------|----------------------|
| Model | IPC2312LE-ADF28KM-WP |
| Brend | Uniview |
| Növ | IP |
| Meqapixel | 2 MP |
| İşıqlandırma | LED |
| İşıqlandırma məsafəsi | 30 m |
| Mikrofon | Mic |
| Obyektiv | Sabit |
| Fokus | 2.8mm |
| Qoruma | IP67 |
| Material | Metal |
| Yaddaş | MicroSD |
| İş mühiti | Outdoor |



Specification

| | | | | | |
|----------------------|---|---------------|----------------|--------------|-------------------|
| IPC2312LE-ADF28KM-WP | | | | | |
| Camera | | | | | |
| Sensor | 1/2.7", 2.0 megapixel, progressive scan, CMOS | | | | |
| Minimum Illumination | Colour: 0.0003lux (F1.0, AGC ON) | | | | |
| Shutter | Auto/Manual, 1 ~ 1/100000s | | | | |
| Adjustment angle | Pan: 0° ~ 360° | | Tilt: 0° ~ 90° | | Rotate: 0° ~ 360° |
| WDR | 120dB | | | | |
| S/N | >52dB | | | | |
| Lens | | | | | |
| Lens | 2.8mm@F1.0 | | | | |
| Iris | Fixed | | | | |
| Field of View (H) | 99.0° | | | | |
| Field of View (V) | 53.0° | | | | |
| Field of View (D) | 118.0° | | | | |
| DORI | | | | | |
| DORI Distance | Lens (mm) | Detect@m | Observe@m | Recognize@m | Identify@m |
| | 2.8 | 45.0(147.6ft) | 18.0(59.1ft) | 9.0(29.5ft) | 4.5(14.8ft) |
| | 4.0 | 64.3(210.9ft) | 25.7(84.4ft) | 12.9(42.2ft) | 6.4(21.1ft) |

| | |
|-------------------------|--|
| Illuminator | |
| Warm Light Range | Up to 30m (98ft) |
| Light On/Off Control | Auto/Manual |
| Video | |
| Video Compression | Ultra265, H.265, H.264, MJPEG |
| H.264 code profile | Baseline profile, Main profile, High profile |
| Frame Rate | Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; |
| Video Bit Rate | 128 Kbps~6144Kbps |
| U-code | Support |
| OSD | Up to 4 OSDs |
| Privacy Mask | Up to 4 areas |
| ROI | Up to 8 areas |
| Video Stream | Dual streams |
| Image | |
| White Balance | Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 |
| Digital noise reduction | 2D/3D DNR |
| Smart Illumination | Support |
| Flip | Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise |
| Dewarping | N/A |
| HLC | Support |
| BLC | Support |
| Defog | Digital Defog |
| Events | |
| Basic Detection | Cross line, intrusion(based on human body detection),Motion detection, Ultra motion detection, Tampering alarm, Audio Detection |
| General Function | Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication, HTTP authentication |
| Audio | |
| Audio Compression | G.711U, G.711A |
| Audio Bitrate | 64 Kbps |
| Two-way audio | N/A |
| Suppression | Support |
| Sampling Rate | 8KHZ |
| Storage | |
| Edge Storage | Micro SD, up to 512GB |
| Network Storage | ANR, NAS(NFS) |
| Network | |
| Protocols | IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS |
| Compatible Integration | ONVIF (Profile S, Profile G, Profile T), API,SDK |
| User/Host | Up to 32 users. 2 user levels: administrator and common user |
| Security | Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF |
| Client | EZStation EZView EZLive |
| Web Browser | Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above |
| Interface | |
| Audio I/O | N/A |
| Alarm I/O | N/A |
| Serial Port | N/A |
| Built-in Mic | Support |

| | |
|------------------------|---|
| Built-in Speaker | N/A |
| WIFI | N/A |
| Network | 1 * RJ45 10M/100M Base-TX Ethernet |
| Video Output | N/A |
| Certifications | |
| EMC | CE-EMC (EN 55032,EN 61000-3-3,EN IEC 61000-3-2,EN 50130) FCC (FCC 47 CFR part15 B) |
| Safety | CE-LVD (EN 62368-1) UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1) |
| Environment | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU) |
| Protection | IP67 (IEC 60529) |
| General | |
| Power | DC 12V±25%, PoE (IEEE 802.3af) |
| | Power consumption: Max 2.8W |
| Power Interface | Ø 5.5mm coaxial power plug |
| Dimensions (L x W x H) | 206 x 73 x 73mm (8.1" x 2.9" x 2.9") |
| Weight | 0.47kg(1.04lb) |
| Material | Graphene + Metal |
| Working Environment | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| Storage Environment | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| surge protection | 4KV |
| Reset Button | Support |