

# IPC2322SB-HDZK-I0

IPC2322SB-HDZK-I0 2MP 2.7-13.5mm WDR Lighthunter IR 50m Network Bullet Kamera UNV



## Specifications

Model	IPC2322SB-HDZK-I0
Brand	Uniview
Növ	IP
Meqapixel	2 MP
Obyektiv	Motorized
Fokus	2.7 - 13.5mm
???qland?rma	IR
???qland?rma m?saf?si	50 m
Mikrofon	Mic
Qoruma	IP67
Material	Metal
Yadda?	MicroSD
?? mühiti	Outdoor

## KEY FEATURES

IPC2322SB-HDZK-I0

## Camera

Sensor 1/2.8", 2.0 megapixel, progressive scan, CMOS

Min. Illumination Colour:0.001 lux (F1.2, AGC ON)  
0 lux with IR

Day/Night IR-cut filter with auto switch (ICR)

Shutter Auto/Manual, 1 ~ 1/100000s

WDR 120dB

S/N &gt;52dB

## Lens

Lens type 2.7~13.5mm@F1.2, AF automatic focusing and motorized zoom lens

Iris Fixed

Field of View (H) 98.2°~30.6°

Field of View (V) 53.3°~17.3°

Field of View (D) 127.7°~37.6°

## DORI

DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.7	70.9(232.5ft)	28.4(93.0ft)	14.2(46.5ft)	7.1(23.3ft)
	13.5	247.5(812.0ft)	99.0(324.8ft)	49.5(162.4ft)	24.8(81.2ft)

## Illuminator

IR Range Up to 50m (164 ft) IR range

Wavelength 850nm

IR On/Off Control Auto/Manual

## Video

Video Compression Ultra 265, H.265, H.264, MJPEG

Frame Rate Main Stream: 1080P (1920\*1080),Max 60fps;  
Sub Stream: 1080P (1920\*1080), Max 60fps;  
Third Stream: D1 (720\*576), Max 60fps

Video Bit Rate 128 Kbps~16 Mbps

ROI Up to 8 areas

Video stream Triple streams

OSD Up to 8 OSDs

Privacy Mask Up to 4 areas per scene

## Image

White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2

Digital noise reduction 2D/3D DNR

Smart IR Support

Flip Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise

HLC Support

BLC Support

Defog Digital Defog

## Intelligent

<b>Smart intrusion prevention</b>	Support false alarm filtering: Cross Line detection, Intrusion detection, Enter Area detection, Leave Area detection
<b>Statistical Analysis Events</b>	People counting, support people flow counting and crowd density monitoring
<b>Basic Detection</b>	Motion detection, Audio detection, Tampering alarm
<b>General Function</b>	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
<b>Audio</b>	
<b>Audio Compression</b>	G.711U, G.711A
<b>Audio Bitrate</b>	64 Kbps
<b>Two-way Audio</b>	Support
<b>Suppression</b>	Support
<b>Sampling Rate</b>	8KHZ
<b>Storage</b>	
<b>Edge Storage</b>	Micro SD, up to 256 GB
<b>Network Storage</b>	ANR,NAS(NFS)
<b>Network</b>	
<b>Protocols</b>	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS
<b>Compatible Integration</b>	ONVIF (Profile S, Profile G, Profile T), API, SDK
<b>User/Host</b>	Up to 32 users. 3 user levels: administrator, operator and common user
<b>Security</b>	Password protection, strong password, HTTPS encryption, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
<b>Client</b>	EZStation EZLive EZview
<b>Web Browser Interface</b>	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above
<b>Audio I/O</b>	1/1
<b>Alarm I/O</b>	1/1
<b>Video output</b>	1 BNC(For debugging)
<b>Network Certification</b>	1 * RJ45 10M/100M Base-TX Ethernet
<b>EMC</b>	CE-EMC (EN 55032: 2015+A1:2020,EN 61000-3-3: 2013+A1: 2019,EN IEC 61000-3-2: 2019+A1: 2021,EN 55035: 2017+A11:2020) FCC (FCC CFR 47 part15 B, ANSI C63.4-2014)
<b>Safety</b>	CE LVD (EN 62368-1:2014+A11:2017) CB (IEC 62368-1:2014) UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01)
<b>Environment Protection</b>	CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)
<b>General</b>	
<b>Power</b>	DC12V(±25%), PoE(IEEE 802.3af) Power consumption: Max 8W
<b>Power Interface</b>	Ø 5.5mm coaxial power plug
<b>Dimensions (L x W x H)</b>	245.0x86.0x85.0mm (9.6"x3.4"x3.4")
<b>Weight</b>	0.92kg(2.03lb)
<b>Working</b>	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)