

IPC2324LB-ADZK-G

IPC2324LB-ADZK-G 4MP 2.8-12mm Motorized Lens Built-in Mic HD IR Bullet Network Kamera UNV



Specifications

Model	IPC2324LB-ADZK-G
Brand	Uniview
Növ	IP
Meqapixel	4 MP
Obyektiv	Motorized
Fokus	2.7 - 13.5mm
???qland?rma	IR
???qland?rma m?saf?si	50 m
Mikrofon	Mic
Qoruma	IP67
Material	Metal
Yadda?	MicroSD
?? mühiti	Outdoor

KEY FEATURES

IPC2324LB-ADZK-G

Camera

Sensor 1/3", 4.0 megapixel, progressive scan, CMOS

Minimum Illumination Colour: 0.003Lux (F1.6, AGC ON)

Illumination 0Lux with IR on

Day/Night IR-cut filter with auto switch (ICR)

Shutter Auto/Manual, 1 ~ 1/100000s

Adjustment angle Pan: 0° ~ 360° Tilt: 0° ~ 90° Rotate: 0° ~ 360°

S/N >56dB

WDR 120dB

Lens

Lens Type 2.8 ~ 12mm, AF automatic focusing and motorized zoom lens

Lens Mount Φ 14

Angle of View (H) 102.79° ~ 30.86°

Angle of View (V) 54.50° ~ 17.49°

Angle of View (O) 106.94° ~ 35.49°

DORI

DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	63.0	25.2	12.6	6.3
	12	270.0	108.0	54.0	27.0

Illuminator

IR Range Up to 50m (164ft) IR range

Wavelength 850nm

IR On/Off Control Auto/Manual

Video

Video Ultra 265, H.265, H.264, MJPEG

Compression

H.264 code profile Baseline profile, Main profile, High profile

Frame Rate Main Stream: 4MP (2688*1520), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps;
Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;

Video Bit Rate 128 Kbps~16 Mbps

U-code Supported

9:16 Corridor Supported

Mode

OSD Up to 4 OSDs

Privacy Mask Up to 4 areas

ROI Up to 8 areas

Motion Detection Up to 4 areas

Image

White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2

Image Setting	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser
Digital noise reduction	2D/3D DNR
Smart IR	Supported
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise
Dewarping	N/A
HLC	Supported
BLC	Supported
Defog	Digital Defog
Audio	
Audio	G.711
Compression	
Suppression	Supported
Sampling Rate	8KHZ
Storage	
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR,NAS(NFS)
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL/TLS, QoS, 802.1x, SNMP
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API , SDK
User/Host	Up to 32 users. 2 user levels: administrator and common user
Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Client	EZStation EZView EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+
Interface	
Network	1 * RJ45 10M/100M Base-TX Ethernet
Built-in Mic	Supported
Certification	
EMC	FCC: FCC Part 15
Safety	CE: EN 60950-1 UL: UL60950-1 IEC 60950-1
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 8.5W
Power Interface	Ø 5.5mm coaxial power plug
Dimensions (L × W206 × 74 × 74mm (8.1" × 2.9" × 2.9") × H)	
Weight	0.55kg (1.2lb)
Material	metal
Working	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Environment	
Storage	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Environment	