

# IPC2K24SE-ADF40KMC-WL-I0

IPC2K24SE-ADF40KMC-WL-I0 4MP 4MM,256GB micro SD card,Built-in speaker Dual Bullet Network Kamera UNV



## Specifications

|                       |                          |
|-----------------------|--------------------------|
| Model                 | IPC2K24SE-ADF40KMC-WL-I0 |
| Brand                 | Uniview                  |
| Növ                   | IP                       |
| Meqapixel             | 4 MP                     |
| Mikrofon              | Mic                      |
| Obyektiv              | Sabit                    |
| Fokus                 | 4mm                      |
| ???qland?rma          | İR                       |
| ???qland?rma m?saf?si | 30 m                     |
| Qoruma                | IP67                     |
| Material              | Metal                    |
| Yadda?                | MicroSD                  |
| ?? mühiti             | Outdoor                  |

## KEY FEATURES

IPC2K24SE-ADF40KMC-WL-I0

## Camera

Sensor 1/2.9"CMOS

Minimum Illumination Colour: 0.0005 lux (F1.0, AGC ON)

## Illumination

Shutter Auto/Manual, 1 ~ 1/100000s

Adjustment angle Pan: 0° ~ 360°

Tilt: 0° ~ 90°

Rotate: 0° ~ 360°

WDR DWDR

S/N &gt;56dB

## Lens

Lens 2 \* 4.0mm@F1.0

Iris Fixed

Field of View (H) 160.00°±10°

Field of View (V) 43.22°

Field of View (D) 180.13°±10°

## DORI

| DORI Distance | Lens (mm) | Detect@m | Observe@m | Recognize@m | Identify@m |
|---------------|-----------|----------|-----------|-------------|------------|
|               | 4.0       | 64.3     | 25.7      | 12.9        | 6.4        |

## Illuminator

LED Distance Up to 30m (98ft)

LEDs Number 2

LED On/Off Auto/Manual

## Control

## Video

Video Ultra265, H.265, H.264, MJPEG

## Compression

H.264 code profile Baseline profile, Main profile, High profile

Frame Rate Main Stream: 4MP (3840\*1080), Max 25fps Human Body Detection off  
Sub Stream: 1920\*540, Max 25fps

Video Bit Rate 128 Kbps~16 Mbps

U-code Support

OSD Up to 8 OSDs

Privacy Mask Up to 4 areas

ROI Up to 8 areas

Video Stream Double streams

## Image

White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2

Digital noise reduction 2D/3D DNR

Smart Illumination Support

Flip N/A

Dewarping N/A

HLC Support

|                               |  |
|-------------------------------|--|
| <b>BLC</b>                    | Support  |
| <b>Defog</b>                  | Digital Defog  |
| <b>Events</b>                 |  |
| <b>Basic Detection</b>        | Human Body Detection ,motion detection, tampering alarm, audio detection   |
| <b>General Function</b>       | Watermark, IP address filtering, Alarm input, Alarm output, access policy, ARP protection, RTSP authentication, user authentication  |
| <b>Audio</b>                  |  |
| <b>Audio</b>                  | G.711  |
| <b>Compression</b>            |  |
| <b>Audio Bitrate</b>          | 64 Kbps  |
| <b>Two-way audio</b>          | Support  |
| <b>Suppression</b>            | Support  |
| <b>Sampling Rate</b>          | 8KHZ   |
| <b>Storage</b>                |  |
| <b>Edge Storage</b>           | Micro SD, up to 256GB  |
| <b>Network Storage</b>        | ANR, NAS(NFS)  |
| <b>Network</b>                |  |
| <b>Protocols</b>              | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS, SSH  |
| <b>Compatible Integration</b> | ONVIF (Profile S, Profile G, Profile T), API,SDK   |
| <b>User/Host</b>              | Up to 32 users. 2 user levels: administrator and common user   |
| <b>Security</b>               | Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF |
| <b>Client</b>                 | EZStation<br>EZView<br>EZLive  |
| <b>Web Browser</b>            | Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below<br>Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+   |
| <b>Interface</b>              |  |
| <b>Audio I/O</b>              | Input: impedance 35kΩ; amplitude 2V [p-p]<br>Output: impedance 600Ω; amplitude 2V [p-p]  |
| <b>Alarm I/O</b>              | 1/1  |
| <b>RS485</b>                  | N/A  |
| <b>Built-in Mic</b>           | Built-in two mics  |
| <b>Built-in Speaker</b>       | Support  |
| <b>WIFI</b>                   | N/A  |
| <b>Network</b>                | 1 * RJ45 10M/100M Base-TX Ethernet   |
| <b>Video Output</b>           | N/A  |
| <b>Certifications</b>         |  |
| <b>EMC</b>                    | CE-EMC (EN 55032: 2015+A1:2020,EN 61000-3-3: 2013+A1: 2019,EN IEC 61000-3-2: 2019+A1: 2021,EN 55035: 2017+A11:2020)<br>FCC (FCC CFR 47 part15 B, ANSI C63.4-2014)  |
| <b>Safety</b>                 | CE LVD (EN 62368-1:2014+A11:2017)<br>CB (IEC 62368-1:2014)<br>UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01)   |
| <b>Environment</b>            | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)   |
| <b>Protection</b>             | IP67 (IEC 60529:1989+AMD1:1999+AMD2:2013)<br>IK10 (IEC 62262:2002)   |
| <b>General</b>                |  |
| <b>Power</b>                  | DC 12V±25%, PoE (IEEE 802.3af)   |