

# IPC6422SR-X25-VF-B

IPC6422SR-X25-VF-B 2MP 25x Motorized LightHunter, Network PTZ Kamera UNV



## Specifications

Model	IPC6422SR-X25-VF-B
Brand	Uniview
Növ	IP
Meqapixel	2 MP
Obyektiv	PTZ
Fokus	2.7 - 13.5mm
???qland?rma	İR
???qland?rma m?saf?si	100m
Mikrofon	Mic
Qoruma	IP67
Material	Plastik
Yadda?	MicroSD
?? mühiti	Outdoor

## KEY FEATURES

Camera	IPC6422SR-X25-VF-B				
Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS				
Min. Illumination	Colour: 0.001 Lux (F1.5, AGC ON) 0 Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual, 1 ~ 1/100000s				
WDR	120dB				
S/N	>52dB				
Lens					
Lens type	5 ~ 125mm, AF automatic focusing and motorized zoom lens				
Digital Zoom	16				
Optical Zoom	25				
Iris	Auto; F1.5 ~ F4.0				
Field of View (H)	54.37° ~ 2.68°				
Field of View (V)	32.23° ~ 1.51°				
Field of View (D)	66.88° ~ 3.16°				
DORI					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	5	77.6 (254.5ft)	31.0 (101.8ft)	15.5 (50.9ft)	7.8 (25.5ft)
	125	1939.7 (6363.7ft)	775.9 (2545.5ft)	387.9 (1272.7ft)	194.0 (636.4ft)
Illuminator					
IR Range	Up to 100m (328 ft) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Video					
Video	Ultra 265, H.265, H.264, MJPEG				
Compression					
Frame Rate	Main Stream: 2MP(1920*1080),Max 60fps; Sub Stream: 2MP (1920*1080), Max 60fps; Third Stream: D1 (720*576), Max 60fps;				
Video Bit Rate	128 Kbps~16 Mbps				
U-code	Support				
ROI	Support				
Video Stream	Triple streams				
OSD	Up to 8 OSDs				
Privacy Mask	24 areas, up to 4 areas per scene				
Image					
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital Noise Reduction	2D/3D DNR				
Smart IR	Support				
Flip	Normal/Flip Vertical/Flip Horizontal/180°				
HLC	Support				

<b>BLC</b>	Support
<b>Defog</b>	Digital Defog
<b>Events</b>	
<b>Basic Detection</b>	Motion detection, Audio detection, Tampering Alarm
<b>Auto Tracking</b>	Support
<b>General Function</b>	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
<b>Audio</b>	
<b>Audio</b>	G.711U,G.711A
<b>Compression</b>	
<b>Audio Bitrate</b>	64 Kbps
<b>Two-way Audio</b>	Support
<b>Suppression</b>	Support
<b>Sampling Rate</b>	8 kHz
<b>Storage</b>	
<b>Edge Storage</b>	Micro SD, up to 256 GB
<b>Network Storage</b>	ANR,NAS(NFS)
<b>Network</b>	
<b>Protocols</b>	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS
<b>Compatible Integration</b>	ONVIF (Profile S, Profile G, Profile T), API,SDK
<b>User/Host</b>	Up to 32 users. 3 user levels: administrator, operator and common user
<b>Security</b>	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
<b>Client</b>	EZStation EZLive EZView
<b>Web Browser</b>	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above
<b>Pan &amp; Tilt</b>	
<b>Pan Range</b>	360° (endless)
<b>Pan Speed</b>	0.1°/s ~ 200°/s Preset speed: 240°/s
<b>Tilt Range</b>	-15° ~ 90° (auto reverse)
<b>Tilt Speed</b>	0.1°/s ~ 120°/s Preset speed: 200°/s
<b>Number of Presets</b>	1024
<b>Preset Patrol</b>	16 patrols, up to 64 presets for each patrol
<b>Route Patrol</b>	16 patrols, up to 32 actions for each patrol
<b>Recorded Patrol</b>	16 patrols, up to 128 actions for each patrol
<b>Patrol Stay Time</b>	15s ~ 1800s
<b>Preset Image Freeze</b>	Support
<b>Home Position</b>	Support
<b>Interface</b>	
<b>Audio I/O</b>	1/1
<b>Alarm I/O</b>	2/1
<b>Serial Port</b>	1 RS485
<b>Built-in Mic</b>	N/A