eurotech
Taste of technology

**TEXNIKI SƏNƏD**

29.11.2026

UNIVIEW

# IPC6422SR-X25-VF-B

Kod: 00-00004921 · Kamera




IPC6422SR-X25-VF-B 2MP 25x Motorized LightHunter, Network PTZ Kamera UNV

## Texniki göstəricilər

| | |
|---|---|
| **IP**<br>Növ | **2 MP**<br>Meqapixel |
| **PTZ**<br>Obyektiv | **2.7 - 13.5mm**<br>Fokus |
| **İR**<br>İşıqlandırma | **100m**<br>İşıqlandırma məsafəsi |
| **Mic**<br>Mikrofon | **IP67**<br>Qoruma |
| **Plastik**<br>Material | **MicroSD**<br>Yaddaş |

**Outdoor**
İş mühiti

## Ətraflı məlumat

| | | | | | |
|---|---|---|---|---|---|
| **Camera** | **IPC6422SR-X25-VF-B** | | | | |
| Sensor | 1/2.8", 2.0 megapixel, progressive scan, CMOS | | | | |
| Min. Illumination | Colour: 0.001 Lux (F1.5, AGC ON)<br>0 Lux with IR | | | | |
| Day/Night | IR-cut filter with auto switch (ICR) | | | | |
| Shutter | Auto/Manual, 1 ~ 1/100000s | | | | |
| WDR | 120dB | | | | |
| S/N | >52dB | | | | |
| **Lens** | | | | | |
| Lens type | 5 ~ 125mm, AF automatic focusing and motorized zoom lens | | | | |
| Digital Zoom | 16 | | | | |
| Optical Zoom | 25 | | | | |
| Iris | Auto; F1.5 ~ F4.0 | | | | |
| Field of View (H) | 54.37° ~ 2.68° | | | | |
| Field of View (V) | 32.23° ~ 1.51° | | | | |
| Field of View (D) | 66.88° ~ 3.16° | | | | |
| **DORI** | | | | | |
| DORI Distance | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) |
| | 5 | 77.6 (254.5ft) | 31.0 (101.8ft) | 15.5 (50.9ft) | 7.8 (25.5ft) |
| | 125 | 1939.7 (6363.7ft) | 775.9 (2545.5ft) | 387.9 (1272.7ft) | 194.0 (636.4ft) |
| **Illuminator** | | | | | |
| IR Range | Up to 100m (328 ft) IR range | | | | |
| Wavelength | 850nm | | | | |

| | |
|---|---|
| IR On/Off Control | Auto/Manual |
| **Video** | |
| Video Compression | Ultra 265, H.265, H.264, MJPEG |
| Frame Rate | Main Stream: 2MP(1920*1080),Max 60fps;<br>Sub Stream: 2MP (1920*1080), Max 60fps;<br>Third Stream: D1 (720*576), Max 60fps; |
| Video Bit Rate | 128 Kbps~16 Mbps |
| U-code | Support |
| ROI | Support |
| Video Stream | Triple streams |
| OSD | Up to 8 OSDs |
| Privacy Mask | 24 areas, up to 4 areas per scene |
| **Image** | |
| White Balance | Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 |
| Digital Noise Reduction | 2D/3D DNR |
| Smart IR | Support |
| Flip | Normal/Flip Vertical/Flip Horizontal/180° |
| HLC | Support |
| BLC | Support |
| Defog | Digital Defog |
| **Events** | |
| Basic Detection | Motion detection, Audio detection, Tampering Alarm |
| Auto Tracking | Support |
| General Function | Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication,<br>User Authentication |
| **Audio** | |

| | |
|---|---|
| Audio Compression | G.711U,G.711A |
| Audio Bitrate | 64 Kbps |
| Two-way Audio | Support |
| Suppression | Support |
| Sampling Rate | 8 kHz |
| **Storage** | |
| Edge Storage | Micro SD, up to 256 GB |
| Network Storage | ANR,NAS(NFS) |
| **Network** | |
| Protocols | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS |
| Compatible Integration | ONVIF (Profile S, Profile G, Profile T), API,SDK |
| User/Host | Up to 32 users. 3 user levels: administrator, operator and common user |
| Security | Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF |
| Client | EZStation<br>EZLive<br>EZView |
| Web Browser | Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above |
| **Pan & Tilt** | |
| Pan Range | 360° (endless) |
| Pan Speed | 0.1°/s ~ 200°/s |
| | Preset speed: 240°/s |
| Tilt Range | –15° ~ 90° (auto reverse) |
| Tilt Speed | 0.1°/s ~ 120°/s |
| | Preset speed: 200°/s |

| | |
|---|---|
| Number of Presets | 1024 |
| Preset Patrol | 16 patrols, up to 64 presets for each patrol |
| Route Patrol | 16 patrols, up to 32 actions for each patrol |
| Recorded Patrol | 16 patrols, up to 128 actions for each patrol |
| Patrol Stay Time | 15s ~ 1800s |
| Preset Image Freeze | Support |
| Home Position | Support |
| **Interface** | |
| Audio I/O | 1/1 |
| Alarm I/O | 2/1 |
| Serial Port | 1 RS485 |
| Built-in Mic | N/A |
| Built-in Speaker | N/A |
| WIFI | N/A |
| Network | 1 * RJ45 10M/100M Base-TX Ethernet |
| Video Output | 1 BNC |
| **Certification** | |
| EMC | CE-EMC (EN 55032:2015+A11:2020+A1:2020,EN 61000-3-3:2013+A1:2019+A2:2021,EN IEC 61000-3-2: 2019+A1: 2021,EN 55035: 2017+A11:2020)<br>FCC (47 CFR Part 15, Subpart B□ ANSI C63.4-2014) |
| Safety | CE LVD (EN 62368-1:2014+A11:2017)<br>CB (IEC 62368-1:2014)<br>UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01) |
| Environment | CE-RoHS (2011/65/EU;(EU)2015/863) |
| Protection | IP67 (IEC 60529:1989+AMD1:1999+AMD2:2013)<br>IK10 (IEC 62262:2002) |
| **General** | |

| | |
|---|---|
| Power | DC12V(±25%, 3A), PoE+(IEEE 802.3at) |
| | Power consumption: MAX 21W |
| Power Interface | Ø 5.5mm coaxial power plug |
| Dimensions (Ø x H) | Ø166 x 295mm (Ø6.5” x 11.6”) |
| Weight | 3.05kg(6.72lb) |
| Working Environment | -40℃ ~ 70℃ (-40°F ~ 158°F)， Humidity: ≤95% RH (non-condensing) |
| Storage Environment | -40℃ ~ 70℃ (-40°F ~ 158°F)， Humidity: ≤95% RH (non-condensing) |
| Surge Protection | 6KV |
| Reset Button | Support |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az