

IPC675LFW-AX4DUPKC-VG

IP CAM UNIVIEW IPC675LFW-AX4DUPKC-VG, 5MP, Mini PTZ, LightHunter, Active Deterrence, 120 dB Optical WDR, PoE (IEEE 802.3af) support, Audio (Mikrofon), Speaker



Specifications

Model	IPC675LFW-AX4DUPKC-VG
Brand	Uniview
Növ	IP
Meqapixel	5 MP
Obyektiv	PTZ
Fokus	2.7 - 13.5mm
???qland?rma	IR
???qland?rma m?saf?si	50 m
Mikrofon	Mic
Qoruma	IP66
Material	Plastik
Yadda?	MicroSD
?? mühiti	Outdoor

KEY FEATURES

IPC675LFW-AX4DUPKC-VG

Camera

Sensor 1/2.7" progressive scan, 5.0 megapixel, CMOS**Min. Illumination** Colour:0.002 lux (F1.2,AGC ON)
0 lux with IR**Day/Night** IR-cut filter with auto switch (ICR)**Shutter** Auto/Manual, shutter time: 1 s ~ 1/100000 s**WDR** 120dB**S/N** >52dB

Lens

Lens type 2.8~12mm, AF automatic focusing and motorized zoom lens**Optical Zoom** 4X**Iris** Fixed; F1.2**Field of View (H)** 106.9° ~ 30.6°**Field of View (V)** 56.0° ~ 17.7°**Field of View (D)** 139.0° ~ 37.6°

DORI

DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8mm	63.0 (206.7ft)	25.2 (82.7ft)	12.6 (41.3ft)	6.3 (20.7ft)
	12mm	270.0 (885.8ft)	108.0 (354.3ft)	54.0 (177.2ft)	27.0 (88.6ft)

Illuminator

IR Range Up to 50m (164ft)**Warm Light Range** Up to 10m (33ft)**Wavelength** 850nm**IR On/Off Control** Auto/Manual

Video

Video Compression Ultra 265, H.265, H.264, MJPEG**Frame Rate** Main Stream: 5MP (2880*1620), Max 30fps
Sub Stream: 720P (1280*720), Max 30fps
Third Stream: D1 (720*576), Max 30fps**Video Bit Rate** 128 Kbps~16 Mbps**ROI** Support**Video Stream** Triple streams**OSD** Up to 8 OSDs**Privacy Mask** Up to 4 areas

Image

White Balance Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2**Digital Noise Reduction** 2D/3D DNR

Smart IR

Smart IR Support**Flip** Normal/Flip Vertical/Flip Horizontal/180°**HLC** Support**BLC** Support

Defog	Digital Defog
Events	
Basic Detection	Motion detection, Audio detection, Tampering Alarm
Auto Tracking	Support
General Function	Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio	
Audio Compression	G.711U,G.711A
Two-way Audio	Support
Suppression	Support
Sampling Rate	16 kHz
Storage	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR,NAS(NFS)
Network	
Protocols	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP , PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP , 802.1x , SNMP, SSL
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Client	EZStation EZLive EZView
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above
Pan & Tilt	
Pan Range	0° ~ 345°
Pan Speed	0.1°/s ~ 50°/s Preset speed: 50°/s
Tilt Range	-10° ~ 110°
Tilt Speed	0.1°/s ~ 40°/s Preset speed: 40°/s
Number of Presets	256
Preset Patrol	16 patrols, up to 64 presets for each patrol
Patrol Stay Time	120s ~ 1800s
Home Position	Support
Interface	
Built-in Mic	Support
Built-in Speaker	Support
Network	1 * RJ45 10M/100M Base-TX Ethernet
Alarm Light	Support
Certification	
EMC	CE-EMC (EN55032:2015, EN55024:2010+A1:2015, EN55035:2017, EN61000-3-2:2014, EN61000-3-3:2013) FCC (FCC CFR 47 part15 B, ANSI C63.4-2014)
Safety	CE LVD (EN 62368-1:2014+A11:2017) CB (IEC 62368-1:2014) UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01)
Environment	CE-ROHS (2011/65/EU;(EU)2015/863)
Protection	IP66 (IEC 60529:1989+AMD1:1999+AMD2:2013)
General	
Power	DC12V(±25%), PoE(IEEE 802.3af)
	Power consumption: MAX 18W
Power Interface	Ø 5.5mm coaxial power plug