eurotech
Taste of technology

TEXNIKI SƏNƏD

22.11.2026

UNIVIEW

IPC9312LFW-AF28-2X4

Kod: 00-00003621 · Kamera



IPC9312LFW-AF28-2X4 2*2MP 4x Lighthunter Dual-lens Built-in 2*mic & speaker Network PTZ CAM UNV

Texniki göstəricilər

IP Növ	**2 MP** Meqapixel
PTZ Obyektiv	**Mic** Mikrofon
IP66 Qoruma	**Plastik** Material
MicroSD Yaddaş	**Outdoor** İş mühiti
50 m İşıqlandırma məsafəsi	**İR** İşıqlandırma

Ətraflı məlumat

	IPC9312LFW-AF28-2X4				
Camera	**Panorama**			**Detail**	
Sensor	1/2.8", 2MP, CMOS				
Min. Illumination	Color:0.002 lux (F1.6, AGC ON) 0 lux with IR			Color:0.002 lux (F1.6, AGC ON) 0 lux with IR/Warm light	
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual, 1~1/100000s				
WDR	120dB			DWDR	
S/N	□ 52dB				
Lens					
Lens type	2.8mm@F1.6			2.8~12mm@F1.6, AF automatic focusing and motorized zoom lens	
Optical Zoom	N/A			4X	
Iris	Fixed aperture				
Field of View (H)	102.4°			106.6° ~ 30.6°	
Field of View (V)	54.9°			56.5° ~ 17.4°	
Field of View (D)	133.1°			138.6° ~ 37.6°	
DORI					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8(Panorama)	43.4(142.5ft)	17.4(57.0ft)	8.7(28.5ft)	4.3(14.3ft)
	2.8(Detail)	43.4(142.5ft)	17.4(57.0ft)	8.7(28.5ft)	4.3(14.3ft)
	12(Detail)	162.9(534.6ft)	65.2(213.8ft)	32.6(106.9ft)	16.3(53.5ft)
Illuminator					
IR Range	Up to 10m (32.8 ft)			Up to 50m (164.0 ft)	

Warm Light Range	N/A	Up to 10m (32.8 ft)
Wavelength	850nm (IR)	
Light On/Off Control	Auto/Manual	
Video		
Video Compression	Ultra 265, H.265, H.264, MJPEG	
Frame Rate	Main Stream: 1080P (1920*1080),Max 25fps Sub Stream: 720P (1280*720),Max 25fps	
Video Bit Rate	128 Kbps~16 Mbps	
U-code	Support (Main stream)	
ROI	Up to 8 areas	
Video stream	Dual streams	
OSD	Up to 4 OSDs	
Privacy Mask	24 areas, up to 4 areas per scene	
Image		
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2	
Digital noise reduction	2D/3D DNR	
Smart IR	Support	
Flip	Normal/Vertical Flip/Horizontal Flip/180°	
HLC	Support	
BLC	Support	
Defog	Digital defog	
Events		
Basic Detection	Motion detection, Audio detection	
General Function	Watermark, IP Address Filtering, Access Policy, ARP Protection, RTSP Authentication, User Authentication	

Audio		
Audio Compression	G.711U, G.711A	
Audio Bitrate	64 Kbps	
Two-way Audio	Support	
Suppression	Support	
Sampling Rate	8 kHz	
Storage		
Edge Storage	Micro SD, up to 256 GB	
Network Storage	ANR	
Network		
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS	
Compatible Integration	ONVIF (Profile S, Profile G), API, SDK	
User/Host	Up to 32 users. 3 user levels: administrator, operator and common user	
Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF	
Client	EZStation EZLive EZView	
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above	
Pan & Tilt		
Pan Range	N/A	0° ~ 345°
Pan Speed	N/A	1°/s ~ 40°/s
	Preset speed: N/A	Preset speed: 40°/s

Tilt Range	18° ± 5°	-10° ~ 100°
Tilt Speed	N/A	1°/s ~ 50°/s
	Preset speed: N/A	Preset speed: 50°/s
Number of Presets	256	
Preset Patrol	16 patrol routes, up to 64 presets for each route	
Patrol Stay Time	1000s~1800s	
Preset Image Freeze	N/A	
Home Position	Support	
Interface		
Audio I/O	N/A	
Alarm I/O	N/A	
Serial Port	N/A	
Built-in Mic	Support (Mic*2)	
Built-in Speaker	Support	
Wi-Fi	N/A	
Network	1 * RJ45 10M/100M Base-TX Ethernet	
Video Output	N/A	
Certification		
EMC	CE-EMC (EN55032:2015; EN55024:2010+A1:2015; EN61000-3-2:2014; EN61000-3-3:2013) FCC (FCC CFR 47 part15 B, ANSI C63.4-2014)	
Safety	CE LVD (EN 62368-1:2014+A11:2017; EN 62368-1:2014) CB (IEC 62368-1:2014) UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01)	
Environment	CE-ROHS (2011/65/EU)	
Protection	IP66 (IEC 60529:1989+AMD1:1999+AMD2:2013)	
General		
Power	DC12V, PoE+(IEEE 802.3at)	

Power consumption: MAX 16W	
Power Interface	Ø 5.5mm coaxial power plug
Dimensions (Ø x H)	Wall Mount: Φ134 x 192 x 302mm (Φ5.3” x 7.6” x 11.9”) Ceiling Mount: Φ134 x 154 x 363mm (Φ5.3” x 6.1” x 14.3”)
Weight	1.03kg (2.27lb)
Working Environment	-20℃ ~ 60℃(-4°F ~ 140°F)， Humidity: ≤95% RH (non-condensing)
Storage Environment	-30℃ ~ 70℃(-22°F ~ 158°F)， Humidity: ≤95% RH (non-condensing)
Surge protection	2KV
Reset button	Support

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az