

IPC94144SFW-X25-F40C

IPC94144SFW-X25-F40C 2MP 25x 4MP+4MP Lighthunter Dual-lens Network PTZ Kamera UNV, 120db WDR



Specifications

Model	IPC94144SFW-X25-F40C
Brand	Uniview
Növ	IP
Meqapixel	4 MP
Obyektiv	PTZ
Fokus	2.7 - 13.5mm
???qland?rma	İR
???qland?rma m?saf?si	100m
Mikrofon	Mic
Qoruma	IP66
Material	Plastik
Yadda?	MicroSD
?? mühiti	Outdoor

KEY FEATURES

IPC94144SFW-X25-F40C					
Camera	Panorama			Detail	
Sensor	1/1.8", 4MP, CMOS			1/2.7", 4MP, CMOS	
Min. Illumination	Color:0.0005 lux (F1.0, AGC ON) 0 lux with warm light			Color:0.003 lux (F1.5, AGC ON) 0 lux with IR	
Day/Night	N/A			IR-cut filter with auto switch (ICR)	
Shutter	Auto/Manual, 1 ~ 1/100000s				
WDR	120dB				
S/N	≥56dB				
Lens					
Lens type	4mm@F1.0			4.8~120mm@F1.5, AF automatic focusing and motorized zoom lens	
Optical Zoom	N/A			25X	
Iris	Fixed aperture; F1.0			Auto; F1.5(W)~F3.8(T)	
Field of View (H)	94.9°			55.46° ~ 3.09°	
Field of View (V)	51.5°			32.94° ~ 1.73°	
Field of View (D)	116.7°			68.22° ~ 3.65°	
DORI					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4 (Panorama)	62.1 (203.6 ft)	24.8 (81.5 ft)	12.4 (40.7 ft)	6.2 (20.4 ft)
	4.8 (Detail)	123.8 (406.0 ft)	49.5 (162.4 ft)	24.8 (81.2 ft)	12.4 (40.6 ft)
	120 (Detail)	2475.0 (8120.1 ft)	990.0 (3248.0 ft)	495.0 (1624.0 ft)	247.5 (812.0 ft)
Illuminator					
IR Range	N/A			Up to 100m (328.1 ft)	
Warm Light Range	Up to 30m (98.4 ft)			N/A	
Wavelength	N/A			850nm (IR)	
Light On/Off Control	Auto/Manual				
Video Compression					
Frame Rate	Main Stream: 4MP (2688*1520),Max 30fps; Sub Stream: 1080P (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps;			Main Stream: 4MP (2688*1520),Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; Third Stream: D1 (720*576), Max 30fps;	
Video Bit Rate	128 Kbps ~ 16 Mbps				
U-code	Support				
ROI	Up to 8 areas				
Video stream	Triple streams				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 4 areas per scene			24 areas, up to 4 areas per scene	
Image					
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				

Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Flip Vertical/Flip Horizontal/180°
HLC	Support
BLC	Support
Defog	Digital defog
Events	
Basic Detection	Motion detection, Audio detection, Tampering Alarm
Auto Tracking	N/A Support
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio	
Audio	G.711U, G.711A
Compression	
Audio Bitrate	64 Kbps
Two-way Audio	Support
Suppression	Support
Sampling Rate	8 kHz
Storage	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
User/Host	Up to 32 users. 3 user levels: administrator, operator and common user
Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Client	EZStation EZLive EZView
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above
Pan & Tilt	
Pan Range	N/A 360°
Pan Speed	N/A 0.1°/s ~ 80°/s
	Preset speed: N/A Preset speed: 80°/s
Tilt Range	18° ± 5° -15° ~ 90°
Tilt Speed	N/A 0.1°/s ~ 80°/s
	Preset speed: N/A Preset speed: 80°/s
Number of Presets	1024
Preset Patrol	16 patrols, up to 64 presets for each patrol
Route Patrol	16 patrols, up to 32 actions for each patrol
Recorded Patrol	16 patrols, up to 128 actions for each patrol
Patrol Stay Time	15s~1800s
Preset Image	N/A
Freeze	
Home Position	Support