UNIVIEW

IPC94144SFW-X25-F40C

Kod: 00-00004922 · Kamera



IPC94144SFW-X25-F40C 2MP 25x 4MP+4MP Lighthunter Dual-lens Network PTZ Kamera UNV, 120db WDR

Texniki göstəricilər

IP Növ	**4 MP** Meqapixel
PTZ Obyektiv	**2.7 - 13.5mm** Fokus
İR İşıqlandırma	**100m** İşıqlandırma məsafəsi
Mic Mikrofon	**IP66** Qoruma
Plastik Material	**MicroSD** Yaddaş

Outdoor
İş mühiti

Ətraflı məlumat

	IPC94144SFW-X25-F40C				
Camera	**Panorama**	**Detail**			
Sensor	1/1.8", 4MP, CMOS	1/2.7", 4MP, CMOS			
Min. Illumination	Color:0.0005 lux (F1.0, AGC ON) 0 lux with warm light	Color:0.003 lux (F1.5, AGC ON) 0 lux with IR			
Day/Night	N/A	IR-cut filter with auto switch (ICR)			
Shutter	Auto/Manual, 1 ~ 1/100000s				
WDR	120dB				
S/N	□ 56dB				
Lens					
Lens type	4mm@F1.0	4.8~120mm@F1.5, AF automatic focusing and motorized zoom lens			
Optical Zoom	N/A	25X			
Iris	Fixed aperture; F1.0	Auto; F1.5(W)~F3.8(T)			
Field of View (H)	94.9°	55.46° ~ 3.09°			
Field of View (V)	51.5°	32.94° ~ 1.73°			
Field of View (D)	116.7°	68.22° ~ 3.65°			
DORI					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4 (Panorama)	62.1 (203.6 ft)	24.8 (81.5 ft)	12.4 (40.7 ft)	6.2 (20.4 ft)
	4.8 (Detail)	123.8 (406.0 ft)	49.5 (162.4 ft)	24.8 (81.2 ft)	12.4 (40.6 ft)
	120 (Detail)	2475.0 (8120.1 ft)	990.0 (3248.0 ft)	495.0 (1624.0 ft)	247.5 (812.0 ft)
Illuminator					
IR Range	N/A	Up to 100m (328.1 ft)			
Warm Light Range	Up to 30m (98.4 ft)	N/A			

Wavelength	N/A	850nm (IR)
Light On/Off Control	Auto/Manual	
Video		
Video Compression	Ultra 265, H.265, H.264, MJPEG	
Frame Rate	Main Stream: 4MP (2688*1520),Max 30fps; Sub Stream: 1080P (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps;	Main Stream: 4MP (2688*1520),Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; Third Stream: D1 (720*576), Max 30fps;
Video Bit Rate	128 Kbps ~ 16 Mbps	
U-code	Support	
ROI	Up to 8 areas	
Video stream	Triple streams	
OSD	Up to 8 OSDs	
Privacy Mask	Up to 4 areas per scene	24 areas, up to 4 areas per scene
Image		
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2	
Digital noise reduction	2D/3D DNR	
Smart IR	Support	
Flip	Normal/Flip Vertical/Flip Horizontal/180°	
HLC	Support	
BLC	Support	
Defog	Digital defog	
Events		
Basic Detection	Motion detection, Audio detection, Tampering Alarm	
Auto Tracking	N/A	Support
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication	
Audio		

Audio Compression	G.711U, G.711A	
Audio Bitrate	64 Kbps	
Two-way Audio	Support	
Suppression	Support	
Sampling Rate	8 kHz	
Storage		
Edge Storage	Micro SD, up to 256 GB	
Network Storage	ANR	
Network		
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS	
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK	
User/Host	Up to 32 users. 3 user levels: administrator, operator and common user	
Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF	
Client	EZStation EZLive EZView	
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above	
Pan & Tilt		
Pan Range	N/A	360°
Pan Speed	N/A	0.1°/s ~ 80°/s
	Preset speed: N/A	Preset speed: 80°/s
Tilt Range	18° ± 5°	-15° ~ 90°
Tilt Speed	N/A	0.1°/s ~ 80°/s
	Preset speed: N/A	Preset speed: 80°/s

Number of Presets	1024
Preset Patrol	16 patrols, up to 64 presets for each patrol
Route Patrol	16 patrols, up to 32 actions for each patrol
Recorded Patrol	16 patrols, up to 128 actions for each patrol
Patrol Stay Time	15s~1800s
Preset Image Freeze	N/A
Home Position	Support
Interface	
Audio I/O	1/1
Alarm I/O	2/1
Serial Port	1 RS485
Built-in Mic	N/A
Built-in Speaker	Support
Wi-Fi	N/A
Network	1 * RJ45 10M/100M Base-TX Ethernet
Video Output	N/A
Certification	
EMC	CE-EMC (EN 55032: 2015+A1:2020,EN 61000-3-3: 2013+A1: 2019,EN IEC 61000-3-2: 2019+A1: 2021,EN 55035: 2017+A11:2020) FCC (FCC CFR 47 part15 B, ANSI C63.4-2014)
Safety	CE LVD (EN 62368-1:2014+A11:2017) CB (IEC 62368-1:2014) UL (UL 62368-1, 2nd Ed., Issue Date: 2014-12-01)
Environment	CE-RoHS (2011/65/EU;(EU)2015/863)
Protection	IP66 (IEC 60529:1989+AMD1:1999+AMD2:2013)
General	
Power	DC12V (±25%), PoE+(IEEE 802.3at)
	Power consumption: MAX 24W

Power Interface	Ø 5.5mm coaxial power plug
Dimensions (Ø x H)	Φ163 x 304mm (Φ6.4” x 12.0”)
Weight	2.27kg (5.00lb)
Working Environment	-40℃ ~ +65℃(-40°F ~ +149°F)， Humidity: ≤95% RH (non-condensing)
Storage Environment	-40℃ ~ +70℃(-40°F ~ +158°F)， Humidity: ≤95% RH (non-condensing)
Surge protection	6KV
Reset button	Support

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az