

LBE5-AC-GEN2

UBIQUITI LITEBEAM AC GEN2 LBE5-AC-GEN2



Specifications

Model	LBE5-AC-GEN2
Brand	Ubiquiti
WIFI	WiFi5
Tezlik	5Ghz
Ötürm? m?saf?si	30 km
PoE	PoE

KEY FEATURES**Specifications**

Dimensions	362 x 273 x 203
Weight	907 g
Housing material	UV resistant plastic for outdoor use
Maximum power consumption	7 W
power unit	24V 0.3A Gigabit PoE Adapter (included)
Nutrition method	Passive Power over Ethernet ("+" 4, 5; "-" 7, 8)
Working temperature	From -40 to +70 °C
Humidity	5 to 95% (with condensation)
Vibration tests	ETSI300-019-1.4
Certificate of conformity	FCC 15.247, IC, CE
CPU	Atheros MIPS 74K
RAM	64 MB
Network interface	(1) 10/100/1000 Ethernet Port
Operating range	5170 – 5875 MHz (802.11ac)
Coverage area	Up to 30 km when placed externally (depending on the base station antenna)
Antenna	Feeder (integrated into the radio system) with a reflector.
Polarization	Depending on the position of the device
Gain	23 dBi
SWR	1.5:1