LS1008G

TP-Link LS1008G 8-portlu gigabit switch ev, ofis və kiçik şəbəkələr üçün ideal seçimdir. Plug-and-play quraşdırma, 802.3x flow control, Auto-MDI/MDIX və enerji qənaətli "Green Ethernet" texnologiyası ilə daha az enerji sərfiyyatı təmin edir. Plastik korpuslu, stolüstü və ya divara asılma üçün uyğundur.

Specifications

Model	LS1008G
Brand	Tp-Link
Port say?	8 Port
Port sür?ti	1000mb/s

KEY FEATURES

HARDWARE FEATURES	
Standards and Protocols	IEEE 802.3i/802.3u/ 802.3ab/802.3x
Interface	8× 10/100/1000Mbps, Auto-Negotiation, Auto-MDI/MDIX Ports
Fan Quantity	Fanless
External Power Supply	External Power Adapter • V1, V3: 9VDC / 0.6A • V2: 5VDC / 0.6A
Dimensions (W x D x H)	5.0 × 2.6 × 0.9 in. (127 × 66.5 × 23 mm)
Max. Power Consumption	3.9W
Max Heat Dissipation	13.299 BTU/h
PERFORMANCE	
Switching Capacity	16 Gbps
Packet Forwarding Rate	11.9 Mpps
MAC Address Table	4K
Packet Buffer Memory	1.5 Mb
Jumbo Frame	16 KB
SOFTWARE FEATURES	
Advanced Features	Green Technology 802.3X Flow Control Back Pressure
Transmission Method	Store and Forward
OTHERS	
Certification	CE, FCC, RoHS
Package Content	8-Port 10/100/1000Mbps Desktop Switch Power Adapter Installation Guide
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40⬚~60⬚ (-40⬚~140⬚) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5%~90% non-condensing