

# M1300 (1-PACK)

Cudy M1300(1-Pack) AC1200 Wi-Fi Gigabit Mesh Solution



## Specifications

Model	M1300 (1-Pack)
Brand	Cudy
WIFI	WiFi5
Geni?lik	Dual band
Mesh	Mesh
Tezlik	2.4Ghz/5Ghz
PoE	PoE
Qo?ulma say?	100+

KEY FEATURES

<b>Model Name</b>	<b>M1300 2.0</b>
<b>CPU Details</b>	<b>880 MHz Dual-Core, MIPS1004Kc</b>
<b>Flash/ROM</b>	<b>16 MB (128 Mbit) NOR</b>
<b>DDR/RAM</b>	<b>128 MB (1 Gbit) DDR3</b>
<b>5 GHz Wi-Fi Speed</b>	<b>867 Mbps</b>
<b>2.4 GHz Wi-Fi Speed</b>	<b>300 Mbps</b>
<b>5 GHz Wi-Fi Streams</b>	<b>2T2R (2×2 MIMO)</b>
<b>2.4 GHz Wi-Fi Streams</b>	<b>2T2R (2×2 MIMO)</b>
<b>Wi-Fi Antennas</b>	<b>4× Internal</b>
<b>5 GHz Antenna Gain Max</b>	<b>6.04dBi</b>
<b>2.4 GHz Antenna Gain Max</b>	<b>4.22dBi</b>
<b>FEM or PA/LNA</b>	<ul style="list-style-type: none"> <li>• 5 GHz: 2× Internal</li> <li>• 2.4 GHz: 2× Internal</li> </ul>
<b>Range Performance</b>	<p>Max: 120 m (394 ft)</p> <p>Indoor WiFi range varies depending on the layout and wall materials. See Wall Performance spec for placement suggestions.</p>
<b>Wall Performance</b>	<p>Two wooden walls with thickness &lt; 3.8 cm (1.5")</p> <p>One concrete wall with thickness &lt; 20 cm (7")</p>
<b>Wi-Fi Transmission Power</b>	<ul style="list-style-type: none"> <li>• CE: <ul style="list-style-type: none"> <li>&lt;20 dBm (2.4 GHz)</li> <li>&lt;23 dBm (5.15 GHz ~ 5.35 GHz)</li> </ul> </li> <li>• FCC: <ul style="list-style-type: none"> <li>&lt;24 dBm (5.25 GHz ~ 5.35 GHz &amp; 5.47 GHz ~ 5.725 GHz)</li> <li>&lt;30 dBm (2.4 GHz &amp; 5.15 GHz ~ 5.25 GHz)</li> </ul> </li> </ul>
<b>Gigabit RJ45 Ports</b>	<b>2</b>
<b>Ethernet Notes</b>	<b>Port 1 as default WAN port, both as LAN ports on Mesh satellite units</b>
<b>LED</b>	<ul style="list-style-type: none"> <li>• System</li> <li>• Speed/Link/ACT of Each Ethernet Port</li> </ul>
<b>Physical Buttons</b>	<ul style="list-style-type: none"> <li>• WPS Button</li> <li>• Reset Button</li> </ul>
<b>Power Input</b>	<b>DC Jack</b>
<b>Power Methods</b>	<b>DC</b>
<b>DC</b>	<b>12V 1A</b>
<b>Power Adapter</b>	<p>Input: 100 ~ 240 V, 50/60 Hz AC</p> <p>Output: 12V 1A DC</p>

<b>Environment</b>	<ul style="list-style-type: none"> <li>• <b>Operating Temperature:</b> 0 °C ~ 40 °C (32 °F ~ 104 °F)</li> <li>• <b>Storage Temperature:</b> -40 °C ~ 70 °C (-40 °F ~ 158 °F)</li> <li>• <b>Humidity:</b> 10% ~ 90% non-condensing</li> <li>• <b>Storage Humidity:</b> 5% ~ 95% non-condensing</li> </ul>
<b>Installation</b>	<ul style="list-style-type: none"> <li>• <b>Desktop</b></li> <li>• <b>Wall-Mounting</b></li> </ul>
<b>Basic Power Saving</b>	0
<b>Dimension</b>	<p>Φ110×154.5 mm</p> <p>Φ4.33×6.08 inches</p>
<b>Product Weight</b>	, <ul style="list-style-type: none"> <li>• Main Product</li> <li>• Power Adapter</li> <li>• Ethernet Cable</li> <li>• Installation Guide</li> </ul>
<b>Retail Package Weight</b>	,
<b>Retail Package Dimension</b>	<p>1-Pack:</p> <p>145×130×265 mm</p> <p>5.71×5.12×10.43 inches,2-Pack:</p> <p>330×130×265 mm</p> <p>12.99×5.12×10.43 inches,3-Pack:</p> <p>415×140×248 mm</p> <p>16.34×5.51×9.76 inches</p>
<b>Units per Carton</b>	<ul style="list-style-type: none"> <li>• 1-Pack: 16</li> <li>• 2-Pack: 8</li> <li>• 3-Pack: 4</li> </ul>
<b>Carton Dimension</b>	1-Pack: 57×56×26 cm,2-Pack: 55×54.5×35.3 cm,3-Pack: 53.6×40×28.7 cm
<b>Carton Gross Weight</b>	,