CUDY

M1500(2-Pack)

Kod: 00-00005561 · Access Pointlər



Cudy M1500 (2-Pack) AX1500 Wi-Fi 6 Gigabit Mesh Solution ev və ofis üçün güclü və stabil simsiz şəbəkə yaradır. Wi-Fi 6 texnologiyası daha yüksək sürət, az gecikmə və çoxsaylı cihaz dəstəyi təqdim edir. Geniş əhatə zonası və asan quraşdırma ilə ideal mesh həlldir.

Texniki göstəricilər

WiFi6
WIFI

Dual band
Genişlik

Mesh
Mesh

2.4Ghz/5Ghz
Tezlik

Ətraflı məlumat

Model	M1500 1.0
CPU Details	1 GHz Single-Core CPU
Flash/ROM	16 MB (128 Mbit) NOR
DDR/RAM	128 MB (1 Gbit) DDR3
5 GHz Wi-Fi Speed	1201 Mbps
2.4 GHz Wi-Fi Speed	300 Mbps
5 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
2.4 GHz Wi-Fi Streams	2T2R (2×2 MIMO)
Wi-Fi Antennas	2× Internal
FEM or PA/LNA	• 5 GHz: 2× Internal • 2.4 GHz: 2× Internal
Beamforming	True
Range Performance	Max: 170 m (558 ft) Tested in open-space environments with minimal interference. Actual WiFi range may vary depending on layout and wall materials. Refer to the Wall Performance specifications for placement suggestions.
Wall Performance	Two wooden walls with thickness < 10 cm (4'') One concrete wall with thickness < 20 cm (7'')
Indoor Coverage Reference	2 Pack: 170 m² (1800 sq ft) 3 Pack: 230 m² (2500 sq ft) Applied to wireless backhaul situation. Place in the center of each floor, with a maximum of two obstacles to each room.
Gigabit RJ45 Ports	3
Ethernet Notes	1× WAN port, the rest are LAN ports
LED	System
Physical Buttons	• WPS Button • Reset Button
Power Input	DC Jack

Power Methods	DC
DC Input	12V 1A
Power Adapter	Input: 100 ~ 240 V, 50/60 Hz AC Output: 12V 1A DC
Max Power Consumption (W)	10W
Environment	• Operating Temperature: 0 ℃ ~ 40 ℃ (32 ℉ ~104 ℉) • Storage Temperature: -40 ℃ ~ 70 ℃ (-40 ℉ ~ 158 ℉) • Humidity: 10% ~ 90% non-condensing • Storage Humidity: 5% ~ 95% non-condensing
FCC, CE	
Installation	Desktop
Dimension	Φ110×154.5 mm Φ4.33×6.08 inches
Product Weight	299.1 g (10.55 oz.)
• **M1500** • **Power Adapter** • **Ethernet Cable** • **Installation Guide**	
Retail Package Weight	• 1-Pack | EU: 677.0 g (23.88 oz.) • 2-Pack | EU: 1241.3 g (43.79 oz.) • 3-Pack | EU: 1676.0 g (59.12 oz.)
Retail Package Dimension	1-Pack: 145×130×265 mm 5.71×5.12×10.43 inches,2-Pack: 330×130×265 mm 12.99×5.12×10.43 inches,3-Pack: 380×130×265 mm 14.96×5.12×10.43 inches
Units per Carton	• 1-Pack: 16 • 2-Pack: 8 • 3-Pack: 4

Carton Dimension	• 1-Pack: 57×56×26 cm 22.44×22.05×10.24 inches • 2-Pack: 55×54.5×35.3 cm 21.65×21.46×13.9 inches • 3-Pack: 53.6×40×28.7 cm 21.1×15.75×11.3 inches
Carton Gross Weight	• 1-Pack | EU: 12.1 kg (26.68 lbs) • 2-Pack | EU: 11.2 kg (24.69 lbs) • 3-Pack | EU: 7.6 kg (16.76 lbs)
Carton Net Weight	• 1-Pack | EU: 10.8 kg (23.81 lbs) • 2-Pack | EU: 9.9 kg (21.83 lbs) • 3-Pack | EU: 6.7 kg (14.77 lbs)
Wi-Fi Standards	Wi-Fi 6
Max Wi-Fi Modulation	1024-QAM
Wi-Fi Efficiency	Beamforming
Max Capacity	128
Recommended Client Upper Limit	60
Max Wi-Fi Channel Width	80 MHz
Wi-Fi Security	WPA/WPA2/WPA3
Guest Network	2.4 GHz, 5 GHz
WPS	True
Operation Modes	• Wi-Fi Router • Access Point • Range Extender • WISP • Client
Mesh	Cudy Mesh
Mesh Backhaul	• Wireless Backhaul • Wired Backhaul

Multi-Band Backhaul	True
WAN Mode	• DHCP • Static IP • PPPOE • PPTP • L2TP
QoS	Per-User Rate Limiting
DHCP	• Address Reservation • DHCP Client List • Server
IP Versions	IPv4/IPv6
IPv6 Protocols	• Relay • Dynamic (SLAAC/DHCPv6) • Static (Fixed IP) • Passthrough • 464XLAT • MAP-E • DS-Lite
IPTV/VLAN	• Bridge • Tag VLAN • VoIP VLAN • IPTV VLAN
IGMP	• IGMP Proxy • IGMP Snooping
Forwarding	• Port Forwarding • UPnP • DMZ
Firewall	• SPI Firewall • Block PING

VPN Client	• PPTP • L2TP • Wireguard
DNS Options	• Manual DNS • Rebind Protection • Override Clients' DNS
Wake on LAN	True
Online Detection	True
Parental Controls	• Profiles Settings • Offline Time • Online Time • Pause the Internet • Web Filter
All Devices Management	• Wi-Fi Time Schedule • MAC Filter • IP/MAC Binding
Per-Devices Management	• Internet On/Off • VPN On/Off • Online Time Schedule • Device Rename
Content Management	• Domain Filter • IP Filter
LED Control	True
Local Control Method	• Config Web Page • App Control
Remote Control Method	• Config Page via HTTPS • App Control • TR069/TR098/TR111/TR143/TR181

Firmware Upgrade	• Local Update • App (Over the Air) • Online Update
Reliability	• Timed Reboot • Backup and Restore
Diagnostic Tools	• Diagnosis • Ping • Traceroute • NSLookup • System Log
Languages	• English • Portuguese • Russian • Spanish • Ukrainian • French • Simplified Chinese
Panel	• Internet Status • Mesh Status • Devices Management • WAN Status • LAN Status • WISP Status • Wi-Fi Status • VPN Status • DHCP Server Status • System Version
Charts	• Mesh Topology • Internet Speed • WISP Speed • Wi-Fi Speed

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az