CUDY

MF4 4G

Kod: 00-00003676 · Routerlər



Cudy MF4 4G LTE Mobil Wi-Fi portativ routerdir. Daxilindəki SİM kart yuvası ilə istənilən mobil operatordan interneti qəbul edib, onu Wi-Fi vasitəsilə 10-a qədər cihaza paylaya bilir. Yığcam dizaynı və güclü batareyası ilə səyahətlər və işgüzar səfərlər üçün mükəmməl seçimdir.

Texniki göstəricilər

WiFi4
WIFI

2.4Ghz
Tezlik

4G
LTE

Ətraflı məlumat

Model	4G LTE Mobile Wi-Fi		
Dimensions	97 x 61 x 15.5mm		
Weight	92g		
Form	MiFi / Pocket Router		
Communication System (WAN)	Chipset	Qualcomm MDM9x07 / MDM9x25	
	Frequency Bands	LTE	B1/B3/B7/B8/B20/B38/B40/B41
		UMTS	B1/B3/B8
	Bandwidth	LTE Band	1.4/3/5/10/15/20 MHz
	Modulation	Downlink	QPSK/16-QAM/64-QAM
		Uplink	QPSK/16-QAM
	Antenna	Primary	Internal
		Diversity	Internal, UMTS Optional
	RF Power Level	LTE FDD	Power Class 3 (23 +/-2dBm)
		UMTS	Power Class 3 (24 +1.7/-3.7dBm)
	Data Rate	4G	3GPP R10, Cat. 4, Downlink/Uplink up to 150Mbps/50Mbps
		3G	3GPP R7 Downlink/Uplink up to 42Mbps/5.76Mbps
WLAN	Wi-Fi	Chipset	Realtek 8192ES
		Frequency	2.4GHz
		Protocol	802.11b/g/n
		Channel	1~13
		Antenna	Internal
	Data Rate	802.11b	Up to 11 Mbps
		802.11g	Up to 54 Mbps
		802.11n	Up to 150 Mbps
Feature	Interface	USB	USB2.0
		USIM	Single, 4FF

LED	POWER	Power/Battery Status Indicator
	Network	4G/3G/2G Network Status Indicator
	Wi-Fi	Wi-Fi Status Indicator
WebUI	System	Connection Status
		Statistics
		Samba (optional)
		Device Management
		Power Mangement
	Mobile Service	Automatic APN matching according to USIM
		Auto Data Connection
		PIN/PUK Management
		Network Mode Selection(2G/3G/LTE/Auto)
	Router	USB RNDIS Device
		Up to 10 Wi-Fi users/devices
		DHCP Server
		IPv4/v6

VPN Passthrough		
Firewall		
WPS		
Security via WEP, WPA-PSK, WPA2-PSK		
Wi-Fi Settings		
Battery	Type	Li-ion Polymer Battery
	Capacity	2000mAh
	Endurance	7 hours (normal network situation)
Operation System	Windows	XP/7/8/10
	MAC OS	10.7+
	Linux	Ubuntu 13.04+
	Browser	IE9+, Firefox, Google Chrome, Safari, Opera
Environment	Power Supply	USB, 5V1A
	Working Temperature	0°C to 35°C
	Storage Temperature	-20°C to 60°C
Certification	3GPP Compliance	CE/FCC/GCF, upon customer's requirement
	Meterial	RoHS

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az