

MR80X

MERCUSYS MR80X EU AX3000 Dual-Band Wi-Fi 6 Router – maksimum sürət, güclü əhatə və axıcı onlayn təcrübə! Ev və ofis üçün ideal seçim – indi əldə et!



Specifications

Model	MR80X
Brand	Mercusys
WIFI	WiFi6
Genişlik	Dual band
Port sürəti	1000 mb/s
Tezlik	2.4Ghz/5Ghz
Qoşulma sayı	100+

KEY FEATURES

Category	Details
Wireless Standards	Compatible with 802.11ax/ac/a/b/g/n Wi-Fi standards
WiFi Speeds	2402 Mbps (5 GHz) + 574 Mbps (2.4 GHz)
Reception Sensitivity	11g 6Mbps: -97dBm 11g 54Mbps: -79dBm 11n HT40 MCS7: -74dBm 11n HT20 MCS7: -77dBm 11a 6Mbps: -97dBm 11a 54Mbps: -79dBm 11ac VHT20 MCS8: -75dBm 11ac VHT40 MCS9: -71dBm 11ac VHT80 MCS9: -67dBm 11ax HE20 MCS11: -67dBm 11ax HE40 MCS11: -64dBm 11ax HE80 MCS11: -61dBm
Transmission Power	2.4 GHz < 20dBm (EIRP) 5 GHz < 23dBm (band1, band2) 5 GHz < 30dBm (band3)
Wireless Security	WPA / WPA2-Personal, WPA2 / WPA3-Personal WPA2-Enterprise, WPA/WPA2-Enterprise
Wireless Functions	Enable/Disable Wireless Radio, WMM
Dimensions	8.2 × 6.8 × 1.6 in (208.8 × 171.6 × 41.7 mm)
Interfaces	1× Gigabit WAN Port + 3× Gigabit LAN Ports
Button	Reset/WPS Button
Antenna Type	4× 5 dBi Fixed Omni-Directional Antennas
WAN Type	Dynamic IP / Static IP / PPPoE / L2TP / PPTP
Management	Access Control, Local Management, Remote Management
DHCP	Server, DHCP Client List
NAT Forwarding	Port Forwarding, Port Triggering, UPnP, DMZ
Firewall Security	SPI Firewall, IP and MAC Address Binding
Guest Network	2.4 GHz Guest Network, 5 GHz Guest Network
VPN Server	OpenVPN / PPTP / L2TP / IPSec VPN Server and Clients
Package Contents	• AX3000 Wi-Fi 6 Router MR80X • Power Adapter • Quick Installation Guide • RJ45 Ethernet Cable
Environment	Operating Temperature: 0°C40°C (32°F104°F) Operating Humidity: 10%~90% Non-Condensing Storage Humidity: 5%~90% Non-Condensing