

# MS106LP

MERCUSYS MS106LP UN 6-Port 10/100Mbps Desktop Switch with 4-Port PoE+



## Specifications

|             |          |
|-------------|----------|
| Model       | MS106LP  |
| Brand       | Mercusys |
| Port say?   | 5 Port   |
| PoE         | PoE      |
| PoE gücü    | 60 W     |
| Port sür?ti | 100mb/s  |

## KEY FEATURES

| Category                | Details  |
|-------------------------|--|
| Standards and Protocols | IEEE 802.3x Flow Control   |
| Dimensions              | 99.8 × 98 × 25 mm  |
| PoE Ports               | RJ45<br>Standard: Compliant with 802.3 af/at Powered Devices<br>PoE Ports: Port 1 - Port 4<br>PoE Power Budget: 40 W   |
| Interfaces              | 6× 10/100 Mbps Ports, Auto-Negotiation, Auto MDI/MDIX  |
| External Power Supply   | External Power Adapter (Output: 53.5V/0.81A)   |
| Installation            | Desktop<br>Wall Mount  |
| Data Rates              | 10/100 Mbps at Half Duplex<br>20/200 Mbps at Full Duplex   |
| Jumbo Frame             | 2 KB   |
| MAC Address Table       | 2K   |
| Max Power Consumption   | 1.87W (220 V / 50 Hz, no PD connected)<br>44.8W (220 V / 50 Hz, with 40W PD connected)   |
| Max Heat Dissipation    | 6.34 BTH/h (no PD connected)<br>152.32 BTH/h (with 40W PD connected)   |
| Package Contents        | <ul style="list-style-type: none"><li>• 6-Port 10/100Mbps Desktop Switch with 4-Port PoE+ (MS106LP)</li><li>• Power Adapter</li><li>• Quick Installation Guide</li></ul>     |
| Environment             | Operating Temperature: 0~40 (32~104)<br>Storage Temperature: -40~70 (-40~158)<br>Operating Humidity: 10%~90% RH non-condensing<br>Storage Humidity: 5%~95% RH non-condensing |