

# MT-7059

## PROSKIT MT-7059 NETWORK TESTER



### Specifications

No technical specifications available.

KEY FEATURES

MT-7059 Transmitter specifications

Indicator	LCD 53X25mm,with back light
Tone frequency	225kHz
Max. distance of transmission	2km
Max. distance of cable map	300m
Max. working current	70mA
Tone mode	9 Tone adjustable
Compatible connectors	RJ45(8 pin) RJ11(6 pin) BNC USB IEEE 1394
Continuity test	LCD (SHORT)
Max. signal voltage	1.5Vp-p
Function selection	3 Push button & 1 Power switch
Function and faults LCD display	LCD display (Wiremap Tone Short Noadapter UTP STP Low battery)
Cable map indication	LCD (#1~#8)
Shielded indication	LCD (#9)
Voltage protection	AC 60V / DC 42V
Low battery display	LCD (6.5V)
Battery type	DC 9.0V(NEDA 1604/ 6F22 DC9V x1pcs)
Dimension (LxWxD)	185X80X32mm

MT-7059 Receiver specifications

Frequency	225kHz
The Max. working current	70mA
Ear jack	1
LED illumination	2 LEDs
Battery type	DC 9.0V(NEDA 1604/ 6F22 DC9Vx1)
Dimension (LxWxD)	218X46X29mm

MT-7059 Remote unit specifications

Compatible connectors	RJ-45(8 pin) RJ-11(6 pin) BNC USB IEEE 1394
Dimension (LxWxD)	107X30X24mm