

# MW3575-U-E

## UNV MW3575-U-E 75" Smart Interactive Display



Model	MW3575-U-E
Brend	Uniview
Ölçü	75"
Görüntü imkanı	4K
Tezlik	60Hz
Panel	IPS
Audio	Audio

## Specification

Panel	Description
Backlight	DLED backlight
Panel size	75 inches
Resolution	3840*2160
Brightness (cd/m <sup>2</sup> )	350
Contrast Ratio	1200:1
Response Time (ms)	8
Color Support	1.07B
Viewing Angle (H/V)	178°/178°
System	Description
CPU	RK3588: 4-core A76 (2.4G) + 4-core A55 (1.8G)
CPU Frequency	2.4GHz
RAM/ROM	DDR4: 8GB eMMC: 64GB
System Compatibility	Android 12.0
Touch	Description
Touch Control	Infrared touch screen, 20-point multi-touch at most
Touch Precision (mm)	±1
Recognizable Object	5 points 2mm
Glass	4mm tempered glass, level 7 on Mohs hardness scale, anti-glare
Touch Response Time (ms)	≤10
Touchscreen Input	Opaque objects (e.g. finger, pen, etc.)
Interface	Description

Video Input	3*HDMI IN (4K@60)
Video Output	1*HDMI OUT (4K@60)
Audio Input	1*AUDIO IN
Audio Output	1*AUDIO OUT
Other Interfaces	1*RS232 3* USB 3.0 1* USB Type C 1* USB Type B
Network	2*RJ 45,10M/100M/1000M adaptive Ethernet Interfaces
Audio	Description
Frequency domain	80Hz 20kHz
Speaker	Left channel 17W: 1*treble (8Ω 5W) + 2*bass (4Ω 6W) Right channel 17W: 1*treble (8Ω 5W) + 2*bass (4Ω 6W)
Wi-Fi	Description
WiFi Configuration	Wi-Fi6 + Wi-Fi5 dual-module, supports 5G/2.4G
WiFi Performance	30 m² coverage, 20m transmission distance in open space
Bluetooth	Description
Bluetooth Version	5.2
Bluetooth Performance	10m transmission distance in open space
OSD	Description
Multi-Language	24 (Simplified Chinese Traditional Chinese English Japanese Arabic French Spanish Portuguese German Italian Dutch Polish Korean Catalan Galician Vietnamese Bulgarian Kazakh)
VESA	Description
Wall mount hole (mm)	600*400
Wall mount screw	4-M8 screw hole
General	Description
Power Supply	AC 100 to 240V, 50/60Hz
Overall Power Consumption (W)	≤320 (on without OPS)
Standby Power Consumption (W)	0.5
Product Dimensions (W*H*D)(mm)	720*1035*89
Package Dimensions (W*H*D)(mm)	115*1336*222
Weight(Kg)	Net weight: 50.0 Gross weight:58.8
Operating Temperature	0 to 50°C
Operating Humidity	10% to 90% (non-condensing)
Storage temperature	-20 to 60°C
Storage humidity	0% to 95% (non-condensing)
Accessories Included	1*power cord 2*touch pen 1*quick guide