

## NS M2

Ubiquiti NanoStation M2 10 kilometr və ya daha çox məsafədə simsiz körpülərin çəkilməsi üçün giriş nöqtəsidir. Şüa bucağı 55° olan yüksək performanslı panel WiFi antenası ilə birləşdirilmişdir.



### Specifications

|                 |          |
|-----------------|----------|
| Model           | NS M2    |
| Brand           | Ubiquiti |
| WiFi            | WiFi5    |
| Tezlik          | 2.4Ghz   |
| Ötürmə məsafəsi | 10 km    |
| PoE             | PoE      |

## KEY FEATURES

|                           |   |
|---------------------------|---|
| CPU                       | Atheros MIPS 24KC, 400 MHz  |
| RAM                       | 32 MB SDRAM, 8MB Flash  |
| Network interface         | 2x10/100 BASE-TX (cat.5, RJ-45), Ethernet interface                                     |
| Certificate of conformity | FCC 15.247, IC, CE  |
| Channel width             | 5/10/20/40 MHz  |
| Operating range           | 2412-2462 MHz (802.11b/g/n)   |
| Transmitter power         | 26dBm, +/-2 dB  |
| RX Sensitivity            | 97dBm +/-2 dB   |
| WiFi Antenna              | 10.4~11.2 dBi dual polarization   |
| Coverage area             | Up to 6 km (with minimum channel width)   |
| TCP/IP Bandwidth          | up to 150 Mbit/s +  |
| Maximum power consumption | 8 W   |
| power unit                | 24 V, 0.5 A (12 W). Comes with injector   |
| Nutrition method          | PoE. Voltage is supplied via Ethernet (pair 4 and 5 are positive, 7 and 8 are negative) |
| Vibration tests           | ETSI300-019-1.4   |
| Humidity                  | from 5 to 95% (with condensation)   |
| Working temperature       | from -30 to +80 C   |
| Dimensions                | 29.4 cm x 8 cm x 3 cm   |
| Weight                    | 0.4 kg  |