

# NS M2

Ubiquiti NanoStation M2 10 kilometr və ya daha çox məsafədə simsiz körpülərin çəkilməsi üçün giriş nöqtəsidir. Şüa bucağı 55° olan yüksək performanslı panel WiFi antenası ilə birləşdirilmişdir.



Model	NS M2
Brend	Ubiquiti
WiFi	WiFi5
Tezlik	2.4Ghz
Ötürmə məsafəsi	10 km
PoE	PoE

## Specification

CPU	Atheros MIPS 24KC, 400 MHz
RAM	32 MB SDRAM, 8MB Flash
Network interface	2x10/100 BASE-TX (cat.5, RJ-45), Ethernet interface
Certificate of conformity	FCC 15.247, IC, CE
Channel width	5/10/20/40 MHz
Operating range	2412-2462 MHz (802.11b/g/n)
Transmitter power	26dBm, +/-2 dB
RX Sensitivity	97dBm +/-2 dB
WiFi Antenna	10.4~11.2 dBi dual polarization
Coverage area	Up to 6 km (with minimum channel width)
TCP/IP Bandwidth	up to 150 Mbit/s +
Maximum power consumption	8 W
power unit	24 V, 0.5 A (12 W). Comes with injector
Nutrition method	PoE. Voltage is supplied via Ethernet (pair 4 and 5 are positive, 7 and 8 are negative)
Vibration tests	ETSI300-019-1.4
Humidity	from 5 to 95% (with condensation)
Working temperature	from -30 to +80 C
Dimensions	29.4 cm x 8 cm x 3 cm
Weight	0.4 kg