

NS M2

Ubiquiti NanoStation M2 10 kilometr və ya daha çox məsafədə simsiz körpülərin çəkilməsi üçün giriş nöqtəsidir. Şüa bucağı 55° olan yüksək performanslı panel WiFi antenası ilə birləşdirilmişdir.



Model	NS M2
Brend	Ubiquiti
WiFi	WiFi5
Tezlik	2.4Ghz
Ötürmə məsafəsi	10 km
PoE	PoE

Specification

CPU	Atheros MIPS 24KC, 400 MHz
RAM	32 MB SDRAM, 8MB Flash
Network interface	2x10/100 BASE-TX (cat.5, RJ-45), Ethernet interface
Certificate of conformity	FCC 15.247, IC, CE
Channel width	5/10/20/40 MHz
Operating range	2412-2462 MHz (802.11b/g/n)
Transmitter power	26dBm, +/-2 dB
RX Sensitivity	97dBm +/-2 dB
WiFi Antenna	10.4~11.2 dBi dual polarization
Coverage area	Up to 6 km (with minimum channel width)
TCP/IP Bandwidth	up to 150 Mbit/s +
Maximum power consumption	8 W
power unit	24 V, 0.5 A (12 W). Comes with injector
Nutrition method	PoE. Voltage is supplied via Ethernet (pair 4 and 5 are positive, 7 and 8 are negative)
Vibration tests	ETSI300-019-1.4
Humidity	from 5 to 95% (with condensation)
Working temperature	from -30 to +80 C
Dimensions	29.4 cm x 8 cm x 3 cm
Weight	0.4 kg