

NSW2010-10T-POE-IN

NSW2010-10T-POE-IN 8PoE+2Port 120W Switch UNV



Model	NSW2010-10T-POE-IN
Brend	Uniview
Port sayı	8 Port
PoE	PoE
PoE gücü	120 W
Port sürati	100mb/s

Specification

Model	NSW2010-10T-POE-IN
Ports	10×100Mbps network ports (RJ45),including 8 PoE ports
Standards	IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at
Switching capacity	2Gbps
Forwarding performance	1.49Mpps
Packet Buffer	1.625Mbit
MAC	4K
Dimensions (W×D×H)	220mm x 150mm x 44mm(8.7"×5.9"×1.7")
Weight	<1.22kg
Power supply	AC: 100-240V, 50/60Hz
PoE	802.3at/af
Max. PoE Power	Max capacity: 120W Max capacity for single port: 30W
Cooling Fans	0
Mean Time Between Failure (MTBF)	>50000 hours
Ambient temperature	0°C-45°C (32°F-113°F)
Operating humidity	10%~90% (noncondensing)
Storage humidity	5%~90% (noncondensing)
Indicator	<p>PWR: Steady on: AC input is normal Off: No AC input</p> <p>PoE: Off: No PoE power supply Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal</p> <p>LINK/ACT: Off: No link Steady: Linked at 10/100Mbps Flashing: Transmitting data</p>

Speed:
Off: Linked at 10/100Mbps
On: Linked at 1000Mbps

Working Mode

Default(Normal mode) : All ports can communicate with each other.
EXTEND(Surveillance mode): Transmission distance up to 250 meters.