

# NVR1104HS-P-S3/H

Dahua NVR1104HS-P-S3/H WizSense 4 kanal PoE NVR; 8TB HDD; 4x1080p@30 fps;



## Specifications

Model	NVR1104HS-P-S3/H
Brand	Dahua
Növ	NVR
Kanal say?	4 kanal
PoE d?st?yi	PoE
Meqapixel	8 MP
Max HDD say?	1 HDD
Max HDD h?cmi	8 TB

## KEY FEATURES

Model	NVR1104HS-S3/H
<b>System</b>	
Main processor	Built-in industrial grade processor
operating system	Embedded Linux OS
Operating interface	Internet / work in local graphical interface
<b>Video</b>	
Access channel	4 channels
Network Bandwidth	80 Mbit/s access, 80 Mbit/s storage and 60 Mbit/s forwarding
Permission	8 MP; 5 MP; 4 MP; 3 MP; 1080p; 720p; D1; CIF
Decoding capability	1-channel 8 MP (30 fps) or 1-channel 5 MP (30 fps) or 2-channel 4 MP (30 fps) or 2 channels 3 MP (30 fps) or 4 channels 1080p (30fps)
Video output	1 simultaneous VGA / 1 HDMI video output, maximum resolution 1080p
Multi-screen display	14
Access to third party cameras	Onvif, RTSP
Compression	
Video	Smart H.265+ / H.265 / Smart H.264+ / H.264
Audio	PCM/G711A/G711U/G726/AAC
<b>Net</b>	
Network protocol	HTTP; HTTPS; TCP/IP; IPv4; IPv6; RTSP; UDP; NTP; DHCP; DNS; P2P
Mobile phone access	iDMSS (iOS); gDMSS (Android)
Access standard	ONVIF (profile T / profile S / profile G); CGI; SDK
Browser	Chrome; IE9 or higher; Fire Fox
<b>Playing a recording</b>	
Multi-channel playback	Up to 4 channels
Recording Mode	Recording Mode Priority: Manual Recording > Alarm Recording > Motion Detection Recording > Time Recording
Storage	Local hard drive and network
Backup	USB device
Playback function	1.Play, Pause, Stop, Fast Forward, Fast Rewind, Rewind, Play Frame by Frame 2.Full Screen, Backup (Cut/File), Partial Zoom, Sound On/Off
<b>Anxiety</b>	
General alarm	Motion Detection, Privacy Masking, Video Loss, PIR Alarm, IPC Alarm

Abnormal Alarm	Interface Device Goes Down, Storage Error, Storage Full, IP Address Conflict, MAC Address Conflict, Login Blocked, Network Security Anomaly
Link to Anxiety	Video, Snapshot, Log, Preset, Tour
External port	
HDD	1 SATA 2.0 port, up to 8 TB per hard drive. The maximum capacity of a hard drive depends on the ambient temperature.
USB	1 USB 2.0 front, 1 USB 2.0 rear
HDMI	1
VGA	1
RCA input	1
RCA output	1
Anxiety	No
Net	1 RJ-45 port (10/100 Mbps), 4 RJ-45 ports with PoE (10/100 Mbps)
Certificates	
Certificates	CE/FCC
Environment	
Operating temperature	-10°C to 45°C (+34°F to +113°F)
Storage temperature	0°C to 40°C (+32°F to +104°F)
Operating humidity	10%~93%
Storage Humidity	30%~85%
Electrical properties	
Power supply	DC48V/53V, 1.25A/1.22A
Power consumption	NVR total power ≤ 10W (without HDD) Total PoE output power is 36W, single port maximum output power is 25.5W.
General information	
Mounting type	Desktop
Color	Black
Working height	3000 m (9843 ft)
Dimensions	260 mm × 225 mm × 47.6 mm
Net weight	0.84 kg (1.85 lb)
Gross weight	1.86 kg (4.10 lb)