

NVR1108HS-S3/H

Dahua NVR1108HS-S3/H WizSense 8 kanal NVR; 2x10TB HDD; 4x1080p@30 fps;



Specifications

Model	NVR1108HS-S3/H
Brand	Dahua
Növ	NVR
Kanal say?	8 kanal
Meqapixel	8 MP
Max HDD say?	1 HDD
Max HDD h?cmi	8 TB

KEY FEATURES

Model	NVR1108HS-S3/H
System	
Main processor	Built-in industrial grade processor
operating system	Embedded Linux OS
Operating interface	Internet / work in local graphical interface
Video	
Access channel	8 channels
Network Bandwidth	80 Mbit/s access, 80 Mbit/s storage and 60 Mbit/s forwarding
Permission	8 MP; 5 MP; 4 MP; 3 MP; 1080p; 720p; D1; CIF
Decoding capability	1-channel 8 MP (30 fps) or 1-channel 5 MP (30 fps) or 2-channel 4 MP (30 fps) or 2 channels 3 MP (30 fps) or 4 channels at 1080P (30fps) 8 channels at 720P (30fps)
Video output	1 simultaneous VGA / 1 HDMI video output, maximum resolution 1080p
Multi-screen display	1 / 4 / 8 / 9
Access to third party cameras	Onvif, RTSP
Compression	
Video	Smart H.265+ / Smart H.264+ / H.265 / H.264
Audio	PCM/G711A/G711U/G726/AAC
Net	
Network protocol	HTTP, HTTPS, TCP/IP, IPv4, IPv6, RTSP, UDP, NTP, DHCP, DNS, P2P
Mobile phone access	iDMSS (iOS); gDMSS (Android)
Access standard	ONVIF (profile T / profile S / profile G); CGI; SDK
Browser	Chrome; IE9 or higher; Fire Fox
Playing a recording	
Multi-channel playback	Up to 8 channels
Recording Mode	Recording Mode Priority: Manual Recording > Alarm Recording > Motion Detection Recording > Time Recording
Storage	Local hard drive and network
Backup	USB device
Playback function	1.Play, Pause, Stop, Fast Forward, Fast Rewind, Rewind, Play Frame by Frame 2.Full Screen, Backup (Cut/File), Partial Zoom, Sound On/Off
Anxiety	
General alarm	Motion Detection, Privacy Masking, Video Loss, PIR Alarm, IPC Alarm
Abnormal Alarm	Interface Device Goes Down, Storage Error, Storage Full, IP Address Conflict, MAC Address Conflict, Login Blocked, Network Security Anomaly
Link to Anxiety	Video, Snapshot, Log, Preset, Tour

External port

HDD 1 SATA 2.0 port, up to 8 TB per hard drive. The maximum capacity of a hard drive depends on the ambient temperature.

USB 1 USB 2.0 front, 1 USB 2.0 rear

HDMI 1

VGA 1

RCA input 1

RCA output 1

Anxiety No

Net 1 RJ-45 port (10 / 100 Mbps)

Certificates

Certificates CE/FCC

Environment

Operating temperature -10°C to 45°C (+34°F to +113°F)

Storage temperature 0°C to 40°C (+32°F to +104°F)

Operating humidity 10%~93%

Storage Humidity 30%~85%

Electrical properties

Power supply DC12V, 1.5A

Power consumption NVR total power ≤ 10W (without HDD)

General information

Mounting type Desktop

Color Black

Working height 3000 m (9843 ft)

Dimensions 260 mm × 225 mm × 47.6 mm

Net weight 0.81 kg (1.79 lb)

Gross weight 1.38 kg (3.04 lb)