

NVR2104-S2

Dahua NVR2104-S2 4 kanal NVR; 6TB HDD; 4×1080p@30 fps; 4 kanal perimetr protection; 4 kanal SMD Plus; Bandwidth 80 Mbps;



Model	NVR2104-S2
Brend	Dahua
Növ	NVR
Kanal sayı	4 kanal
Meqapixel	5 MP
Max HDD sayı	1 HDD
Max HDD həcmi	6 TB

Specification

System	
Main Processor	Industrial-grade embedded processor
Operating System	Embedded Linux
Operating Interface	Web; Local GUI
AI	
AI by Camera	Perimeter protection; SMD Plus
Perimeter Protection	
Perimeter Performance of AI by Camera (Number of Channels)	4
SMD Plus	
SMD Plus by Camera	4-channel SMD Plus (AI by camera), secondary filtering for human and motor vehicle SMD Plus, reducing false alarms caused by leaves, rain and lighting condition change
Audio and Video	
Access Channel	4 channels
Network Bandwidth	Access: 80 Mbps; Storage: 80 Mbps; Forward: 60 Mbps
Resolution	5MP; 4MP; 3MP; 2MP; 720p; D1
Decoding Capability	2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps
Video Output	1 × VGA, 1 × HDMI (simultaneous)
Multi-screen Display	1, 4 views
Third-party Camera Access	Onvif
Compression Standard	

Video Compression	Smart H.265; H.265; Smart H.264; H.264
Audio Compression	PCM; G711A; G711U; G726
Network	
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; DDNS; Alarm Server; IP Search (Supports Dahua IP camera, DVR, NVS, etc.); P2P
Mobile Phone Access	Android; iOS
Interoperability	ONVIF (profile T/S/G); CGI; SDK
Browser	Chrome; IE 9 or later; Firefox
Recording Playback	
Multi-channel Playback	Up to 4 channels
Record Mode	Manual record; alarm record; motion detection record; schedule record
Storage Method	Local HDD and network
Backup Method	USB device
Playback Function	1. Play; pause; stop; fast forward; fast backward; rewind; play by frame 2. Full screen; backup (video clip/file); partially zoom in; audio on/off
Alarm	
General Alarm	Motion detection; privacy masking; video loss; PIR alarm
Anomaly Alarm	Camera offline; storage error; disk full; IP conflict; MAC conflict; login lock; cyber security exception
Intelligent Alarm	Perimeter protection; SMD Plus
Alarm Linkage	Recording; snapshot; buzzer; log; preset; email; tour
Port	
Audio Input	1
Audio Output	1
HDD Interface	1 SATA port, up to 6 TB. The maximum HDD capacity varies with environment temperature
USB	2 rear USB 2.0 ports
HDMI	1
VGA	1
Network Port	1 × RJ-45, 10/100 Mbps self-adaptive Ethernet port
General	
Power Supply	12 VDC, 1.5 A
Power Consumption	Total output of NVR is ≤ 10 W (without HDD)
Net Weight	0.42 kg (0.93 lb)
Gross Weight	1.03 kg (2.27 lb)
Product Dimensions	204.6 mm × 206.4 mm × 45.6 mm (8.06" × 8.13" × 1.80") (W × L × H)
Packaging Dimensions	96 mm × 364 mm × 261 mm (3.78" × 14.33" × 10.28") (W × L × H)
Operating Temperature	-10 °C to +55 °C (14 °F to +131 °F)
Operating Humidity	10%–93% (RH)
Installation	Rack or desktop
Certifications	CE: EN62368-1; EN55032; EN55024; EN55035; EN61000-3-2; EN61000-3-3; EN50130-4 FCC: Part 15 Subpart B