

# NVR2104-S2

Dahua NVR2104-S2 4 kanal NVR; 6TB HDD; 4×1080p@30 fps; 4 kanalimetr protection; 4 kanal SMD Plus; Bandwidth 80 Mbps;



## Specifications

Model	NVR2104-S2
Brand	Dahua
Növ	NVR
Kanal say?	4 kanal
Meqapixel	5 MP
Max HDD say?	1 HDD
Max HDD h?cmi	6 TB

## KEY FEATURES

<b>System</b>	
<b>Main Processor</b>	Industrial-grade embedded processor
<b>Operating System</b>	Embedded Linux
<b>Operating Interface</b>	Web; Local GUI
<b>AI</b>	
<b>AI by Camera</b>	Perimeter protection; SMD Plus
<b>Perimeter Protection</b>	
<b>Perimeter Performance of AI by Camera (Number of Channels)</b>	4
<b>SMD Plus</b>	
<b>SMD Plus by Camera</b>	4-channel SMD Plus (AI by camera), secondary filtering for human and motor vehicle SMD Plus, reducing false alarms caused by leaves, rain and lighting condition change
<b>Audio and Video</b>	
<b>Access Channel</b>	4 channels
<b>Network Bandwidth</b>	Access: 80 Mbps; Storage: 80 Mbps; Forward: 60 Mbps
<b>Resolution</b>	5MP; 4MP; 3MP; 2MP; 720p; D1
<b>Decoding Capability</b>	2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps
<b>Video Output</b>	1 × VGA, 1 × HDMI (simultaneous)
<b>Multi-screen Display</b>	1, 4 views
<b>Third-party Camera Access</b>	Onvif
<b>Compression Standard</b>	
<b>Video Compression</b>	Smart H.265; H.265; Smart H.264; H.264
<b>Audio Compression</b>	PCM; G711A; G711U; G726
<b>Network</b>	
<b>Network Protocol</b>	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; DDNS; Alarm Server; IP Search (Supports Dahua IP camera, DVR, NVS, etc.); P2P
<b>Mobile Phone Access</b>	Android; iOS
<b>Interoperability</b>	ONVIF (profile T/S/G); CGI; SDK
<b>Browser</b>	Chrome; IE 9 or later; Firefox
<b>Recording Playback</b>	
<b>Multi-channel Playback</b>	Up to 4 channels
<b>Record Mode</b>	Manual record; alarm record; motion detection record; schedule record
<b>Storage Method</b>	Local HDD and network
<b>Backup Method</b>	USB device
<b>Playback Function</b>	1. Play; pause; stop; fast forward; fast backward; rewind; play by frame 2. Full screen; backup (video clip/file); partially zoom in; audio on/off
<b>Alarm</b>	
<b>General Alarm</b>	Motion detection; privacy masking; video loss; PIR alarm
<b>Anomaly Alarm</b>	Camera offline; storage error; disk full; IP conflict; MAC conflict; login lock; cyber security exception
<b>Intelligent Alarm</b>	Perimeter protection; SMD Plus
<b>Alarm Linkage</b>	Recording; snapshot; buzzer; log; preset; email; tour
<b>Port</b>	
<b>Audio Input</b>	1
<b>Audio Output</b>	1

---

<b>HDD Interface</b>	<b>1 SATA port, up to 6 TB. The maximum HDD capacity varies with environment temperature</b>
<b>USB</b>	<b>2 rear USB 2.0 ports</b>
<b>HDMI</b>	<b>1</b>
<b>VGA</b>	<b>1</b>
<b>Network Port</b>	<b>1 × RJ-45, 10/100 Mbps self-adaptive Ethernet port</b>
<b>General</b>	
<b>Power Supply</b>	<b>12 VDC, 1.5 A</b>
<b>Power Consumption</b>	<b>Total output of NVR is ≤ 10 W (without HDD)</b>
<b>Net Weight</b>	<b>0.42 kg (0.93 lb)</b>
<b>Gross Weight</b>	<b>1.03 kg (2.27 lb)</b>
<b>Product Dimensions</b>	<b>204.6 mm × 206.4 mm × 45.6 mm (8.06" × 8.13" × 1.80") (W × L × H)</b>
<b>Packaging Dimensions</b>	<b>96 mm × 364 mm × 261 mm (3.78" × 14.33" × 10.28") (W × L × H)</b>
<b>Operating Temperature</b>	<b>-10 °C to +55 °C (14 °F to +131 °F)</b>
<b>Operating Humidity</b>	<b>10%–93% (RH)</b>
<b>Installation</b>	<b>Rack or desktop</b>
<b>Certifications</b>	<b>CE: EN62368-1; EN55032; EN55024; EN55035; EN61000-3-2; EN61000-3-3; EN50130-4 FCC: Part 15 Subpart B</b>