

# NVR2108-I2

Dahua NVR2108-I2 8 kanal NVR; 10TB HDD; 6×1080p@30 fps;1 kanal uz tanima; 1 kanal perimetr protection; 4 kanal SMD Plus; Bandwidth 80 Mbps;



## Specifications

Model	NVR2108-I2
Brand	Dahua
Növ	NVR
Kanal say?	8 kanal
Meqapixel	12 MP
Max HDD say?	1 HDD
Max HDD h?cmi	10 TB

## KEY FEATURES

## System

<b>Main Processor</b>	<b>Industrial-grade embedded processor</b>
<b>Operating System</b>	<b>Embedded Linux</b>
<b>Operation Interface</b>	<b>Web; local GUI</b>
<b>AI</b>	
<b>AI by Camera</b>	<b>Face detection; face recognition; perimeter protection; SMD Plus</b>
<b>AI by Device</b>	<b>Face detection; face recognition; perimeter protection; SMD Plus</b>
<b>Perimeter Protection</b>	
<b>Perimeter Performance AI by Device (Number of Channels)</b>	<b>1</b>
<b>Perimeter Performance of AI by Camera (Number of Channels)</b>	<b>4</b>
<b>Face Detection</b>	
<b>Face Attributes</b>	<b>6 attributes: Gender; age group (6); glasses; expressions (8); mouth mask; beard</b>
<b>Face Detection Performance of AI by Device (1080P) (Number of Channels)</b>	<b>1 (up to 12 face images/second)</b>
<b>Face Detection Performance of AI by Camera (Number of Channels)</b>	<b>5</b>
<b>Face Recognition</b>	
<b>Face Database Capacity</b>	<b>Up to 10 face databases with 5,000 images</b>
<b>Face Recognition Performance of AI by Device (1080P) (Number of Channels)</b>	<b>1 (up to 4 face images/second)</b>
<b>Face Recognition Performance of AI by Camera (Number of Channels)</b>	<b>5</b>
<b>SMD Plus</b>	
<b>SMD Plus by Device</b>	<b>4</b>
<b>SMD Plus by Camera</b>	<b>6-channel SMD Plus (AI by camera): Detects tripwire and intrusion of human or vehicle; filters false alarms caused by leaves, raindrops and change of brightness away</b>
<b>Video</b>	
<b>Access Channel</b>	<b>8 channels</b>
<b>Network Bandwidth</b>	<b>80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding.</b>
<b>Resolution</b>	<b>12MP; 8MP; 5MP; 4MP; 3MP; 2MP; 720p; D1</b>
<b>Decoding Capability</b>	<b>AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps</b> <b>AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps</b>
<b>Video Output</b>	<b>1 × VGA, 1 × HDMI (simultaneous)</b>
<b>Multi-screen Display</b>	<b>1, 4, 8, 9 views</b>
<b>Third Party Camera Access</b>	<b>Onvif</b>
<b>Compression</b>	
<b>Video</b>	<b>Smart H.265+; H.265; Smart H.264+; H.264; MJPEG</b>
<b>Audio</b>	<b>PCM; G711A; G711U; G726</b>
<b>Network</b>	
<b>Network Protocol</b>	<b>HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; DDNS; Alarm Server; IP Search (Supports Dahua IP camera, DVR, NVS, etc.); P2P; Auto Registration</b>

Mobile Phone Access	Android; iOS
Interoperability	ONVIF (profile T; profile S; profile G); CGI; SDK
Browser	Chrome; IE9 or later; Firefox
Record Playback	
Multi-channel Playback	Up to 8 channels
Record Mode	Manual record; alarm recordings; motion detection recordings; scheduled recordings
Storage	Local HDD and network
Backup	USB device
Playback Function	1. Play; pause; stop; fast forward; fast backward; rewind; play by frame 2. Full screen; backup (vide clip/file); partially zom in; audio on/off
Alarm	
General Alarm	Motion detection; privacy masking; video loss; PIR alarm; IPC alarm
Anomaly Alarm	Camera offline; storage error; disk full; IP conflict; MAC conflict; login lock; cyber security exception
Intelligent Alarm	Face detection; face recognition; perimeter protection (intrusion and tripwire); IVS; SMD Plus
Alarm Linkage	Recording; snapshot; buzzer; log; preset; email; tour
External Port	
HDD	1 SATA port, up to 10 TB. The maximum HDD capacity varies with environment temperature
USB	2 rear USB 2.0 ports
HDMI	1 (max. resolution: 4K)
VGA	1
Network	1 × RJ-45 (10 or 100 Mbps)
RCA Input	1
RCA Output	1
RCA Output	1
General Parameter	
Power Supply	12 V DC, 1.5 A
Power Consumption	Total output of NVR is ≤ 10 W (without HDD)
Net Weight	0.45 kg (0.99 lb)
Gross weight	1.07 kg (3.04 lb)
Product Dimensions	204.6 mm × 206.4 mm × 48.1 mm (8.06" × 8.13" × 1.89") (W × L × H)
Package Dimensions	96 mm × 364 mm × 261 mm (3.78" × 14.33" × 10.28") (W × L × H)
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Storage Temperature	0 °C to 40 °C (32 °F to 104 °F)
Operating Humidity	10%–93%
Storage Humidity	30%–85%
Operating Altitude	3,000 m (9,842.52 ft)
Installation	Desktop
Certifications	FCC:47 CFR FCC Part15,SubpartB,Class A CE-EMC:EN 55032:2015,Class A;EN IEC 61000-3-2:2019;EN 61000-3-3:2013+A1:2019;EN 55024:2010+A1:2015;EN 55035:2017;EN 50130-4:2011+A1:2014 CE-LVD:EN 62368-1:2014+A11:2017