

# NVR2108-S3

Dahua NVR2108-S3 8 kanal NVR; 16TB HDD; 6×1080p@30 fps;; 4 kanal perimetr protection; 4 kanal SMD Plus; Bandwidth 80 Mbps;



## Specifications

Model	NVR2108-S3
Brand	Dahua
Növ	NVR
Kanal say?	8 kanal
Meqapixel	12 MP
Max HDD say?	1 HDD
Max HDD h?cmi	16 TB

## KEY FEATURES

## System

**Main Processor** Industrial-grade embedded processor**Operating System** Embedded Linux**Operating Interface** Web; Local GUI

## AI

**AI by Camera** Perimeter protection; SMD Plus**Perimeter Protection****Perimeter Performance of AI by Camera (Number of Channels)** 4**SMD Plus****SMD Plus by Camera**

4-channel SMD Plus (AI by camera), secondary filtering for human and motor vehicle SMD Plus, reducing false alarms caused by leaves, rain and lighting condition change

## Audio and Video

**Access Channel** 8 channels**Network Bandwidth** Access: 80 Mbps; Storage: 80 Mbps; Forward: 60 Mbps**Resolution** 12MP; 8MP; 5MP; 4MP; 3MP; 2MP; 720p; D1**Decoding Capability** 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps**Video Output** 1 × VGA, 1 × HDMI (simultaneous)**Multi-screen Display** 1, 4, 8, 9 views**Third-party Camera Access** Onvif**Compression Standard****Video Compression** Smart H.265; H.265; Smart H.264; H.264**Audio Compression** PCM; G711A; G711U; G726

## Network

**Network Protocol** HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; DDNS; Alarm Server; IP Search (Supports Dahua IP camera, DVR, NVS, etc.); P2P**Mobile Phone Access** Android; iOS**Interoperability** ONVIF (profile T/S/G); CGI; SDK**Browser** Chrome; IE 9 or later; Firefox**Recording Playback****Multi-channel Playback** Up to 8 channels**Record Mode** Manual record; alarm record; motion detection record; schedule record**Storage Method** Local HDD and network**Backup Method** USB device**Playback Function**  
1. Play; pause; stop; fast forward; fast backward; rewind; play by frame  
2. Full screen; backup (video clip/file); partially zoom in; audio on/off

## Alarm

**General Alarm** Motion detection; privacy masking; video loss; PIR alarm**Anomaly Alarm** Camera offline; storage error; disk full; IP conflict; MAC conflict; login lock; cyber security exception**Intelligent Alarm** Perimeter protection; SMD Plus**Alarm Linkage** Recording; snapshot; buzzer; log; preset; email; tour

## Port

**Audio Input** 1

---

<b>Audio Output</b>	<b>1</b>
<b>HDD Interface</b>	<b>1 SATA port, up to 16 TB. The maximum HDD capacity varies with environment temperature</b>
<b>USB</b>	<b>2 rear USB 2.0 ports</b>
<b>HDMI</b>	<b>1</b>
<b>VGA</b>	<b>1</b>
<b>Network Port</b>	<b>1 × RJ-45, 10/100 Mbps self-adaptive Ethernet port</b>
<b>General</b>	
<b>Power Supply</b>	<b>12 VDC, 1.5 A</b>
<b>Power Consumption</b>	<b>Total output of NVR is ≤ 10 W (without HDD)</b>
<b>Net Weight</b>	<b>0.42 kg (0.93 lb)</b>
<b>Gross Weight</b>	<b>1.03 kg (2.27 lb)</b>
<b>Product Dimensions</b>	<b>204.6 mm × 206.4 mm × 45.6 mm (8.06" × 8.13" × 1.80") (W × L × H)</b>
<b>Packaging Dimensions</b>	<b>96 mm × 364 mm × 261 mm (3.78" × 14.33" × 10.28") (W × L × H)</b>
<b>Operating Temperature</b>	<b>-10 °C to +55 °C (14 °F to +131 °F)</b>
<b>Operating Humidity</b>	<b>10%–93% (RH)</b>
<b>Installation</b>	<b>Rack or desktop</b>
<b>Certifications</b>	<b>CE: EN62368-1; EN55032; EN55024; EN55035; EN61000-3-2; EN61000-3-3; EN50130-4 FCC: Part 15 Subpart B</b>