

# NVR2108HS-I

Dahua NVR2108HS-I 8 kanal NVR; 16TB HDD; 6x1080p@30 fps;1 kanal uz tanima; 2 kanal perimetr protection; 4 kanal SMD Plus; Bandwidth 80 Mbps;



## Specifications

Model	NVR2108HS-I
Brand	Dahua
Növ	NVR
Kanal say?	8 kanal
Meqapixel	12 MP
Max HDD say?	1 HDD
Max HDD h?cmi	8 TB

## KEY FEATURES

## System

**Main Processor** Industrial-grade embedded processor**Operating System** Embedded Linux**Operation** Web/operating in local GUI

## Interface

## Video

**Access Channel** 8 channels**Network Bandwidth** 80 Mbps for access, 80 Mbps for storage and 60 Mbps for forwarding**Resolution** 12M/8M/5M/4M/3M/2M/720p/D1

## Decoding

**Capability** AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps

AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps

**Video Output** 1 VGA/1 HDMI simultaneous video output by default, the maximum resolution of HDMI is 4K**Multi-screen Display** 1/4/8/9**Third Party Camera Access** Onvif, RTSP

## Compression

**Video** H.264/H.265/Smart H.264+/Smart H.265+/MJPEG**Audio** PCM/G711A/G711U/G26/AAC

## Network

**Network Protocol** HTTP, HTTPS, TCP/IP, IPv4, IPv6, RTSP, UDP, NTP, DHCP, DNS**Mobile Phone Access** Android, iOS**Interoperability** ONVIF (profile T/profile S/profile G), CGI, SDK**Browser** Chrome, IE9 or above, Firefox

## Record Playback

**Multi-channel Playback** Up to 8 channels playback**Record Mode** Priority of record mode: Manual recording > alarm recording > motion detection recording > timed recording**Storage** Local HDD and network**Backup** USB device

## Playback Function

1. Play, pause, stop, fast forward, fast backward, rewind, play by frame
2. Full screen, backup (cut/file), partially enlarge, audio on/off

## SMD Plus

**Performance** 4 channels**AI Search** Search by target classification (human, vehicle)

## Face Recognition

**Performance** Max 8 face pictures/sec processing

1 channel video stream face recognition

<b>Stranger Mode</b>	Detect strangers' faces (not in device's face database). Similarity threshold can be set manually
<b>AI Search</b>	Up to 8 target face images search at same time, similarity threshold can be set for each target face image
<b>Database Management</b>	Up to 10 face databases with 5,000 face images in total. Name, gender, birthday, address, certificate type, certificate No., countries@ions and state can be added to each face picture
<b>Database Application</b>	Each database can be applied to video channels independently
<b>Trigger Events</b>	Buzzer, Voice Prompts, Email, Snapshot, Recording, Alarm Out, PTZ Activation, etc.
<b>Alarm Linkage</b>	Video recording, snapshot, log, preset, tour
<b>Perimeter Protection</b>	
<b>Performance</b>	2 channels
<b>Object classification</b>	Human/Vehicle secondary recognition for tripwire and intrusion
<b>AI Search</b>	Search by target classification (human, vehicle)
<b>Alarm</b>	
<b>General Alarm</b>	Motion detection, privacy masking, video loss, PIR alarm, IPC alarm
<b>Anomaly Alarm</b>	Front-end device going offline, storage error, full storage, IP conflict, MAC conflict, login lock, network security anomaly
<b>Alarm Linkage</b>	Video recording, snapshot, log, preset, tour
<b>External Port</b>	
<b>HDD</b>	1 SATA port, up to 8 TB. The maximum HDD capacity varies with environment temperature
<b>USB</b>	1 front USB 2.0 port, 1 rear USB 2.0 port
<b>HDMI</b>	1
<b>VGA</b>	1
<b>Network</b>	1 RJ-45 port (10/100 Mbps)
<b>RCA Input</b>	1
<b>RCA Output</b>	1
<b>General Parameter</b>	
<b>Power Supply</b>	DC 12V, 1.5A
<b>Power Consumption</b>	Total output of NVR is ≤ 10W (without HDD)
<b>Net Weight</b>	0.81 kg (1.79 lb)
<b>Gross weight</b>	1.38 kg (3.04 lb)
<b>Product Dimensions</b>	260 mm × 232.7 mm × 47.6 mm (W × L × H) 10.24 inch × 9.16 inch × 1.87 inch (W × L × H)
<b>Package Dimensions</b>	89 mm × 333 mm × 315 mm (W × L × H) 3.50 inch × 13.11 inch × 12.40 inch (W × L × H)
<b>Operating Temperature</b>	-10°C to +55°C (+14°F to +113°F)
<b>Storage Temperature</b>	0°C to +40°C (+32°F to +104°F)
<b>Operating Humidity</b>	10%–93%
<b>Storage Humidity</b>	30%–85%
<b>Operating Altitude</b>	3000 m (9843 ft)
<b>Installation</b>	Desktop mounting
<b>Certifications</b>	CE/FCC