

NVR2216-16P-I

Dahua NVR2216-16P-I WizSense 16 kanal PoE NVR; 2x8TB HDD; 4x1080p@30 fps;1 kanal uz tanima; 2 kanal perimetr protection; 4 kanal SMD Plus; Bandwidth 200 Mbps;



Specifications

Model	NVR2216-16P-I
Brand	Dahua
Növ	NVR
Kanal say?	16 kanal
PoE d?st?yi	PoE
Meqapixel	12 MP
Max HDD say?	2 HDD
Max HDD h?cmi	8 TB

KEY FEATURES

System

Main Processor Industrial-grade embedded processor**Operating System** Embedded Linux**Operation** Web/operating in local GUI

Interface

Video

Access Channel 16 channels**Network** 200 Mbps for access, 200 Mbps for storage and 100 Mbps for forwarding

Bandwidth

Resolution 12M/8M/5M/4M/3M/2M/720p/D1

Decoding

Capability AI disabled: 1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps

AI enabled: 1-channel 8MP@30 fps; 1-channel 5MP@30 fps; 2-channel 4MP@30 fps; 4-channel 1080p@30 fps

Video Output 1 VGA/1 HDMI simultaneous video output by default, the maximum resolution of HDMI is 4K**Multi-screen** 1/4/8/9/16

Display

Third Party Onvif, RTSP

Camera Access

Compression

Video H.264/.H265/Smart H.264+/Smart H.265+/MJPEG**Audio** PCM/G711A/G711U/G26/AAC

Network

Network Protocol HTTP, HTTPS, TCP/IP, IPv4, IPv6, RTSP, UDP, NTP, DHCP, DNS**Mobile Phone** Android, iOS

Access

Interoperability ONVIF (profile T/profile S/profile G), CGI, SDK**Browser** Chrome, IE9 or above, Firefox

Record Playback

Multi-channel Up to 16 channels playback

Playback

Record Mode Priority of record mode: Manual recording > alarm recording > motion detection recording > timed recording**Storage** Local HDD and network**Backup** USB device

Playback Function

1. Play, pause, stop, fast forward, fast backward, rewind, play by frame
2. Full screen, backup (cut/file), partially enlarge, audio on/off

SMD Plus

Performance 4 channels**AI Search** Search by target classification (human, vehicle)

Face Recognition

Performance Max 8 face pictures/sec processing

1 channel video stream face recognition

Stranger Mode	Detect strangers' faces (not in device's face database). Similarity threshold can be set manually
AI Search	Up to 8 target face images search at same time, similarity threshold can be set for each target face image
Database Management	Up to 10 face databases with 5,000 face images in total. Name, gender, birthday, address, certificate type, certificate No., countries@ions and state can be added to each face picture
Database Application	Each database can be applied to video channels independently
Trigger Events	Buzzer, Voice Prompts, Email, Snapshot, Recording, Alarm Out, PTZ Activation, etc.
Alarm Linkage	Video recording, snapshot, log, preset, tour
Perimeter Protection	
Performance	2 channels
Object classification	Human/Vehicle secondary recognition for tripwire and intrusion
AI Search	Search by target classification (human, vehicle)
Alarm	
General Alarm	Motion detection, privacy masking, video loss, PIR alarm, IPC alarm
Anomaly Alarm	Front-end device going offline, storage error, full storage, IP conflict, MAC conflict, login lock, network security anomaly
Alarm Linkage	Video recording, snapshot, log, preset, tour
External Port	
HDD	2 SATA ports, up to 8 TB for a single HDD. The maximum HDD capacity varies with environment temperature
USB	1 front USB 2.0 port, 1 rear USB 2.0 port
HDMI	1
VGA	1
Network	1 RJ-45 port (10/100/1000 Mbps), 16 RJ-45 ports with PoE power supply (10/100 Mbps)
RCA Input	1
RCA Output	1
Alarm	Alarm 4 alarm-in ports and 2 alarm-out ports
General Parameter	
Power Supply	100V-240V, 47HZ-63HZ, 3.5A
Power Consumption	Total output of NVR is ≤ 10W (without HDD) Total output power of PoE is 130W, the maximum output power of a single port is 25.5W
Net Weight	2.63 kg (5.80 lb)
Gross weight	3.91 kg (8.62 lb)
Product Dimensions	375 mm × 329.3 mm × 53 mm (W × L × H)
Package Dimensions	14.76 inch × 12.96 inch × 2.09 inch (W × L × H)
Product Dimensions	148 mm × 449 mm × 421 mm (W × L × H)
Package Dimensions	5.83 inch × 17.68 inch × 16.57 inch (W × L × H)
Operating Temperature	-10°C to +55°C (+14°F to +113°F)
Storage Temperature	0°C to +40°C (+32°F to +104°F)
Operating Humidity	10%–93%
Storage Humidity	30%–85%
Operating Altitude	3000 m (9843 ft)
Installation	Desktop mounting
Certifications	CE/FCC