

# NVR301-04LS3-P4

NVR301-04LS3-P4 NVR301-04LS3-P4 4 Channel 4K NVR, IP Network Video Recorder With PoE UNV



## Specifications

Model	NVR301-04LS3-P4
Brand	Uniview
Növ	NVR
Kanal say?	4 kanal
PoE d?st?yi	PoE
Meqapixel	8 MP
Max HDD say?	1 HDD
Max HDD h?cmi	6 TB

## KEY FEATURES

Model	NVR301-04LS3-P4
Video/Audio Input	
IP Video Input	4-ch
Network	
Incoming Bandwidth	64Mbps
Outgoing Bandwidth	48Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SMTP, RTSP
Video/Audio Output	
HDMI/VGA Output	HDMI: 3840x2160/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz VGA: 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Recording Resolution	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Audio Compression	G.711A, G.711U
Synchronous Playback	4-ch
Liveview display	1/4
Corridor Mode Screen	3/4
Snapshot	
FTP/Schedule/Event Snapshot	1-ch snapshot, up to D1 resolution
Decoding	
Decoding format	Ultra 265/H.265/H.264
Liveview/Playback	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	1 x 4K@30, 4 x 5MP@25, 4 x 4MP@25, 4 x 3MP@25, 4 x 1080p@30
Hard Disk	
SATA	1 SATA interface
Capacity	up to 6TB for each disk
Smart	
VCA Detection by Camera	Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, Audio Detection, Ultra Motion Detection(UMD)
VCA Search	Face Search, Behavior Search
Smart Intrusion Prevention (SIP),	Total 4-ch
UMD by Camera	
General Alarm	
General Alarm	Motion, Tampering, Human Body Detection, Video Loss, Alarm Input
Alert Alarm	IP Conflict, Network Disconnected, Disk Offline , Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal
External Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 2 x USB2.0
RS232	NA

---

<b>RS485</b>	<b>NA</b>
<b>Alarm In</b>	<b>NA</b>
<b>Alarm Out</b>	<b>NA</b>
<b>PoE</b>	
<b>Interface</b>	<b>4 RJ45 10M/100M self-adaptive Ethernet Interface</b>
<b>Max Power</b>	<b>Max 30W for single port Max 54W in total</b>
<b>Supported Standard</b>	<b>IEEE 802.3at, IEEE 802.3af</b>
<b>General</b>	
<b>Power Supply</b>	<b>48V DC Power Consumption: ≤9 W (without HDD)</b>
<b>Working Environment</b>	<b>-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)</b>
<b>Dimensions (W×D×H)</b>	<b>205mm × 205mm × 46mm (8.1"×8.1"×1.8 ")</b>
<b>Weight (without HDD)</b>	<b>≤0.6kg (1.32 lb)</b>
<b>Certification</b>	
<b>Certification</b>	<b>CE, FCC, UL, RoHS, WEEE</b>
<b>CE</b>	<b>EN 55032: 2015, EN 61000-3-3: 2013, EN IEC 61000-3-2: 2019, EN 55035: 2017</b>
<b>FCC</b>	<b>Part15 Subpart B, ANSI C63.4</b>