UNIVIEW

# NVR301-04S3

Kod: 00-00004916 · Videoregistrator



NVR301-04S3 4 Channel 4K NVR, IP Network Video Recorder UNV

## Texniki göstəricilər

| | |
|---|---|
| **NVR** | **4 kanal** |
| Növ | Kanal sayı |
| **8 MP** | **1 HDD** |
| Meqapixel | Max HDD sayı |
| **10 TB** | |
| Max HDD həcmi | |

## Ətraflı məlumat

| | NVR301-04S3 |
|---|---|
| **Decoding** | |
| Decoding Format | Ultra 265, H.265, H.264 |
| Decoding Capability | 1 x 4K@30, 4 x 5MP@25, 4 x 4MP@25, 4 x 3MP@25 |
| Decoding Capability Description | The resolution of each channel cannot exceed 4000 pixels in length and 3000 pixels in width |
| Audio Compression | G.711A, G.711U |
| **Network** | |
| Incoming Bandwidth | 64Mbps |
| Outgoing Bandwidth | 48Mbps |
| Remote Users | 128 |
| Protocols | TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SMTP, RTSP, IPv4 |
| Browser(Plugin) | Windows: IE (IE10/ 11), Firefox (version 52.0 and above), Chrome (version 45 and above), Edge (version 79 and above) |
| **Video/Audio Input** | |
| IP Video Input | 4-ch |
| **Video/Audio Output** | |
| HDMI Output | 4K(3840x2160)/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz |
| VGA Output | 1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz |
| 3.5mm Audio Output | 1-ch |
| Liveview Display | 1/4 |
| Corridor Mode Screen | 3/4 |
| **Snapshot** | |
| FTP/Schedule/Event Snapshot | 1-ch snapshot, up to D1 resolution |

| | |
|---|---|
| **Recording** | |
| Recording Resolution | 8MP/6MP/5MP/4MP/3MP/1080P/960P/720P/D1/2CIF/CIF |
| Synchronous Playback in Local | 4-ch |
| **Smart** | |
| VCA Detection by IPC | Face Detection, SIP (Intrusion Detection, Cross Line Detection, Enter Area, Leave Area), Ultra Motion Detection (UMD) |
| VCA Search | Behavior Search |
| Smart by IPC | Total 4-ch(Face Detection, SIP, UMD) |
| Capacity of Snapshot Records | 2 millions records for face snapshot |
| **Alarm** | |
| General Alarm | Auto Tracking, Motion Detection, Tampering, Human Body Detection, Video Loss, Alarm Input, Audio Detection |
| Alert Alarm | IP Conflict, Network Disconnected, Disk Offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal |
| **GUI Language** | |
| GUI Language | 21 languages: Chinese, English, Vietnamese, Thai, Turkish, Spanish (Latin America), Portuguese (Brazil), Spanish, Portuguese, French, German, Italian, Dutch, Polish, Czech, Hungarian, Slovak, Russian, Hebrew, Arabic, Ukrainian |
| **Hard Disk** | |
| SATA | 1 SATA Interface |
| Capacity | Up to 10TB for each HDD(The maximum HDD capacity varies with environment temperature and hard disk size) |
| **External Interface** | |
| Network Interface | 1 RJ45 10M/100M self-adaptive Ethernet Interface |
| USB | Rear panel: 2 x USB2.0 |
| RS485 | N/A |
| RS232 | N/A |
| Alarm In | N/A |

| | |
|---|---|
| Alarm Out | N/A |
| Power Supply | DC 12V/2A |
| **Working Environment** | |
| Working Temperature | -10 °C ~ 55 °C (14 °F ~ 131 °F) |
| Working Humidity | ≤ 90% RH (non-condensing) |
| Power Consumption (without HDD) | ≤ 5W |
| **Dimensions** | |
| Weight (without HDD) | ≤ 0.98Kg (2.16lb) |
| Dimensions | 260mm × 240mm × 46mm (10.2"×9.4"×1.8") |
| **Certification** | |
| Certification | CE; FCC; UL; RoHS; WEEE |
| CE | EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035 |
| FCC | Part15 Subpart B |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az