

# NVR302-32E2

NVR302-32E2 up to 12mp 4K 2-SATA 32CH NETWORK VIDERO RECORDER UNV



## Specifications

Model	NVR302-32E2
Brand	Uniview
Növ	NVR
Kanal say?	32 kanal
Meqapixel	12 MP
Max HDD say?	2 HDD
Max HDD h?cmi	8 TB

## KEY FEATURES

Model	NVR302-09E2	NVR302-16E2	NVR302-32E2
Video/Audio Input			
IP Video Input	9-ch	16-ch	32-ch
Two-way Audio Input	1-ch, RCA		
Network			
Incoming Bandwidth	320Mbps		
Outgoing Bandwidth	180Mbps	320Mbps	
Remote Users	128		
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS		
Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows		
Video/Audio Output			
HDMI/VGA Output	VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz HDMI: 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz		
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF		
Audio Output	1-ch, RCA		
Audio Compression	G.711A, G.711U		
Synchronous Playback	16-ch		
Live View Display	1/4/6/8/9	1/4/6/8/9/16	1/4/6/8/9/16/25/36
Corridor Mode Screen	3/4/5/7/9	3/4/5/7/9/10/12/16	3/4/5/7/9/10/12/16/32
Snapshot			
FTP/Schedule/Event Snapshot	16-ch snapshot, up to 1080P resolution		
Decoding			
Decoding Format	Ultra 265, H.265, H.264		
Live View/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF		
Capability	1 x 12MP@30, 2 x 4K@30, 1 x 12MP@30, 2 x 4K@30, 5 x 5 x 4MP@30, 9 x 1080P@30	4MP@30, 10 x 1080P@30, 16 x 720P@30	1 x 12MP@30, 2 x 4K@30, 5 x 4MP@30, 10 x 1080P@30, 22 x 720P@30, 32 x D1
Hard Disk			
SATA	2 SATA interfaces		
Capacity	Up to 8TB for each disk (The maximum HDD capacity varies with environment temperature)		
eSATA	NA		
Disk Group	Support		
Smart			
VCA Detection by Camera	Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, Defocus Detection, Scene Change Detection, Object Left Behind, Object Removed, Auto Tracking		
VCA Search	Behavior Search, Vehicle Search		
People Counting	People Flow Counting, Crowd Density Monitoring		

**Smart Intrusion Prevention (SIP), Total 8-ch****Vehicle Detection by Camera****General Alarm****General Alarm****Motion, Tampering, Human Body Detection, Video Loss, Input Alarm, Audio Detection****Alert Alarm****IP Conflict, Network Disconnected, Disk Offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal****External Interface****Network Interface****2 RJ45 10M/100M/1000M self-adaptive Ethernet Interfaces****USB Interface****Front panel: 1 x USB2.0, Rear panel: 1 x USB2.0 1 x USB3.0****RS232****NA****RS485****1****Alarm In****8-ch****Alarm Out****2-ch****General****Power Supply****12VDC/3.3A****Power Consumption: ≤ 12 W (without HDD)****Working Environment****-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)****Dimensions (W×D×H)****380mm × 315mm × 53mm (15.0" × 12.4"× 2.1")****Weight (without HDD)****≤1.8Kg (3.97lb)****Certification****Certification****CE, FCC, UL, RoHS, WEEE****CE****EN 55032: 2015, EN 61000-3-3: 2013, EN IEC 61000-3-2: 2019, EN 55035: 2017****FCC****Part15 Subpart B, ANSI C63.4**