

NVR4104-4KS2

Dahua NVR4104-4KS2 4 kanal NVR; 10TB HDD; 8×1080p@30 fps; 4 kanal perimetr protection; 4 kanal SMD Plus; Bandwidth 80 Mbps;



Specifications

Model	NVR4104-4KS2
Brand	Dahua
Növ	NVR
Kanal say?	4 kanal
Meqapixel	8 MP
Max HDD say?	1 HDD
Max HDD h?cmi	10 TB

KEY FEATURES

System

Main Processor Industrial embedded micro-processor**Operating System** Embedded Linux**Operation** Web; local GUI

Interface

Perimeter Protection by Camera**Performance** 4/8/16 channels**AI Search** Search for pictures by channel, time and event type**SMD Plus by Camera****Performance** 4/8/16 channels**AI Search** Search by target classification (human, vehicle)

Video

Access Channel 4/8/16**Network** 80 Mbps for access, 80 Mbps for storage and 48 Mbps for forwarding

Bandwidth

Resolution 8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 1.3MP, 720p, D1, and more**Decoding** 8 channels@1080p (30 fps)

Capability

Video Output HDMI: 3840 × 2160; 1920 × 1080; 1280 × 1024; 1280 × 720
VGA: 1920 × 1080; 1280 × 1024; 1280 × 720**Multi-screen** 4-channel: 1/4**Display** 8-channel: 1/4/8/9
16-channel: 1/4/8/9/16**Third Party** Panasonic, Sony, Samsung, Axis, Pelco, Arecont, ONVIF, Canon and more

Camera Access

Compression

Video Smart H.265+; Smart H.264+; H.265; H.264**Audio** PCM; G.711A; G.711U; G.726

Network

Network Protocol HTTP; HTTPS; TCP/IP; IPv4/IPv6; UPnP; SNMP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; DDNS; FTP; Alarm Server; IP Search (supports Dahua IP camera, DVR, NVS, and more); P2P**Mobile Phone** Android; iOS

Access

Interoperability ONVIF (profile T/S/G); CGI; SDK**Browser** Chrome; IE9 or later; Firefox

Record Playback

Multi-channel 4-channel: 1/4**Playback** 8-channel: 1/4/9
16-channel: 1/4/9/16**Record Mode** Manual; schedule (general; MD; alarm; MD & alarm; intelligent)**Storage Method** Local HDD and network**Backup** USB device**Playback** 1. Play; pause; stop; fast forward; fast backward; rewind; play by frame**Function** 2. Full screen; backup (cut/file) ; partially enlarge; audio on/off

Storage

Disk Group	Yes
Alarm	
General Alarm	Motion detection; privacy masking; video loss; PIR alarm; IPC alarm
Anomaly Alarm	Camera offline; storage error; full storage; IP conflict; MAC conflict; login lock; network security anomaly
Intelligent Alarm	Perimeter protection; SMD; people counting; heat map
Alarm Linkage	Record; snapshot; IPC external alarm output; buzzer; log; preset; email
External Port	
Audio Input	1 channel, RCA connector
Audio Output	1 channel, RCA connector, which support voice intercom output
HDD	1 SATA III port, up to 10 TB for a single HDD. The maximum HDD capacity varies with environment temperature
USB	2 rear USB 2.0 ports
HDMI	1
VGA	1
Network	1 independent 100 Mbps ethernet port
General Parameter	
Power Supply	12V/2A DC
Power Consumption	< 6.3W (without HDD)
Net Weight	0.4 kg (0.88 lb) (without HDD)
Gross Weight	1.5 kg (3.31 lb) (without HDD)
Product Dimensions	204.6 mm × 206.4 mm × 45.6 mm (8.1" × 8.1" × 1.8")
Package Dimensions	361 mm × 259 mm × 94 mm (14.2" × 10.2" × 3.7")
Operating Temperature	-10°C to +55°C (+14°F to +131°F)
Storage Temperature	0°C to +40°C (+32°F to +104°F)
Operating Humidity	10%–93% (RH)
Storage Humidity	30%–85% (RH)
Operating Altitude	3,000 m (9,843 ft)
Certifications	CE: EN55032; EN55024; EN50130-4; EN60950-1 FCC: Part 15 Subpart B; ANSI C63.4-2014 UL: UL 60950-1