eurotech
Taste of technology

TEXNIKI SƏNƏD

11.11.2026

DAHUA

NVR4208-4KS3

Kod: 00-00001977 · Videoregistrator



DAHUA NVR4208-4KS3 8 Channel 1U 4K & H.265 Lite Network Video Recorder

Texniki göstəricilər

NVR
Növ

8 kanal
Kanal sayı

8 MP
Meqapixel

2 HDD
Max HDD sayı

16 TB
Max HDD həcmi

Ətraflı məlumat

Category	Specification
Channels	8 IP camera channels
Max Resolution	Supports IP cameras up to 12 MP; real-time preview/playback up to 4K (3840×2160)
Recording Bandwidth	AI off: 160 Mbps incoming/recording, 80 Mbps outgoing AI on: 80 Mbps incoming/recording, 60 Mbps outgoing
Decoding Capability	AI off: 1×12 MP@30 fps, 2×8 MP@30 fps, 3×5 MP@30 fps, 4×4 MP@30 fps, 8×1080p@30 fps AI on: 1×12 MP, 1×8 MP, 2×5 MP, 3×4 MP, 7×1080p
Video Output	1× HDMI up to 4K & 1× VGA (1080p); simultaneous HDMI+VGA display
Video Compression	Smart H.265+, H.265, Smart H.264+, H.264, MJPEG
AI Features	SMD Plus on 4 channels (by NVR); supports camera AI: face detection/recognition, perimeter protection, people counting, stereo analysis, heat map (on compatible cameras)
Playback	Multi-channel playback up to 8 channels; supports smart playback, event/tag-based search
Storage	2× SATA HDDs, up to 20 TB each
Audio & Alarm I/O	Audio: 1× RCA input, 1× RCA output Alarm: 4 inputs, 2 outputs
Network & USB	1× Gigabit RJ-45; 2× USB 2.0; supports ONVIF 22.12 Profiles S/T/G, CGI/SDK; protocols: HTTP, HTTPS, TCP/IP, UDP, IPv4/6, NTP, DHCP, DNS, SMTP, FTP, DDNS, SNMP, P2P, etc.
Backup & Interface	Backup via USB or network; supports EPTZ, one-click arming/disarming
Power & Consumption	12 V DC, 4 A supply included; consumption < 10 W (no HDD)
Dimensions & Weight	375×283×53 mm; net weight ~1.49 kg; gross ~2.77 kg
Operating Conditions	–10 °C to +55 °C; 10–93 % RH (non-condensing)
Installation	1U rack-mount or desktop use

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az