

# NVR4432-4KS2/I

Dahua NVR4432-4KS2/I WizSense 32 kanal NVR; 4x10TB HDD; 8x1080p@30 fps;8 kanal uz tanima; 8 kanal perimetr protection;4 kanal ANPR; 16 kanal SMD Plus; Bandwidth 256 Mbps;



## Specifications

Model	NVR4432-4KS2/I
Brand	Dahua
Növ	NVR
Kanal say?	32 kanal
Meqapixel	12 MP
Max HDD say?	4 HDD
Max HDD h?cmi	10 TB

## KEY FEATURES

## System

Main Processor Industrial-grade embedded processor

Operating System Embedded Linux

Operation Interface Web; local GUI

## AI

AI by Camera Face detection; face recognition; perimeter protection; SMD Plus; ANPR; people counting; stereo analysis; heat map

AI by Device Face detection; face recognition; perimeter protection; SMD Plus

## Perimeter Protection

Perimeter Performance AI by Device (Number of Channels) 2

Perimeter Performance of AI by Camera (Number of Channels) 8

## Face Detection

Face Attributes 6 attributes: Gender; age group (6); glasses; expressions (8); mouth mask; beard

Face Detection Performance of AI by Device (1080P) (Number of Channels) 1 (up to 12 face images/second)

Face Detection Performance of AI by Camera (Number of Channels) 8

## Face Recognition

Face Database Capacity Up to 10 face databases with 20,000 images

Face Recognition Performance of AI by 1 (up to 4 face images/second) Device (1080P) (Number of Channels)

Face Recognition Performance of AI by 8 Camera (Number of Channels)

## SMD Plus

SMD Plus by Device 4

SMD Plus by Camera 16-channel SMD Plus (AI by camera): Detects tripwire and intrusion of human or vehicle; filters false alarms caused by leaves, raindrops and change of brightness away

## ANPR

ANPR by Camera 4

## Video

Access Channel 32 channels

Network Bandwidth AI off: Access: 256 Mbps; Storage: 256 Mbps; Forward: 256 Mbps

AI on: Access: 160 Mbps; Storage: 160 Mbps; Forward: 160 Mbps

Resolution 16MP; 12MP; 8MP; 5MP; 4MP; 3MP; 1080p; 720p; D1

Decoding Capability AI off: 1 channel × 16MP@20 fps; 1 channel × 12MP@20 fps; 2 channels × 8MP@30 fps; 4 channels × 5MP@30 fps; 5 channels × 4MP@30 fps; 10 channels × 1080p@30 fps

AI on: 1 channel × 16MP@20 fps; 1 channel × 12MP@20 fps; 2 channels × 8MP@30 fps; 3 channel × 5MP@30 fps; 4 channels × 4MP@30 fps; 8 channels × 1080p@30 fps

Video Output 1-ch VGA output and 1-ch HDMI output; simultaneous/heterogeneous video sources output for VGA and HDMI is configurable

Multi-screen Display 1st Screen: 1/4/8/9/16/25/36  
2nd Screen: 1/4/8/9

Third Party Camera Access Panasonic; Sony; Samsung; Axis, Pelco; Arecont; ONVIF; Canon; RTSP

Compression	
Video	Smart H.265+; Smart H.264+; H.265; H.264; MJPEG
Audio	PCM; G.711A; G.711U; G.726
Network	
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4/IPv6; UPnP; SNMP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; PPPoE; DDNS; FTP; Alarm Server; IP Search (Support Dahua IP camera; DVR; NVS; etc.); P2P; auto register
Mobile Phone Access	Android; iOS
Interoperability	ONVIF(profile T/S/G); CGI; SDK
Browser	Chrome; IE9 or later; firefox
Record Playback	
Multi-channel Playback	Up to 16 channels
Record Mode	Manual; schedule (general; MD; alarm; MD & alarm; intelligent)
Storage Method	Local HDD; network
Backup	USB device
Playback Function	1. Play; pause; stop; fast forward; fast backward; rewind; play by frame 2. Full screen; backup (cut/file) ; partially enlarge; audio on/off
Alarm	
General Alarm	Motion detection; privacy masking; video loss; scene changing; PIR alarm; IPC external alarm
Anomaly Alarm	Camera disconnection; storage error; disk full; IP conflict; MAC conflict; login locked; and cybersecurity exception
Intelligent Alarm	Face detection; face recognition; perimeter protection; SMD Plus; people counting; stereo analysis; heat map
Alarm Linkage	Record; snapshot; IPC external alarm output; audio; buzzer; log; preset; email
External Port	
HDD	4 SATA ports, up to 10 TB. The maximum HDD capacity varies with environment temperature
USB	1 front USB 2.0 port, 1 rear USB 3.0 port
HDMI	1 (max. resolution: 4K)
VGA	1
Network	2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet ports
RCA Input	1
RCA Output	1
Alarm Input	16
Alarm Output	4
RS-232	1 channel, used to debug and pass through serial data
RS-485	1 channel, used to control PTZ, and it supports multiple protocols
General Parameter	
Power Supply	Single, 100 V–240 V AC, 50 Hz–60 Hz
Power Consumption	Total output of NVR is ≤ 8 W (without HDD)
Net Weight	4.25 kg (9.35 lb)
Gross Weight	6.48 kg (18.41 lb)
Product Dimensions	440.0 mm × 415.6 mm × 76.0 mm (17.32" × 16.36" × 2.99") (W × L × H)
Package Dimensions	529.0 mm × 499.0 mm × 211.0 mm (20.83" × 19.65" × 9.31") (W × L × H)
Operating Conditions	–10 °C to +55 °C (+10 °F to +131 °F)
Storage Conditions	0 °C to +40 °C (32 °F to 104 °F)
Operating Humidity	10%–93%
Storage Humidity	30%–85%
Operating Altitude	3,000 m (9,842.52 ft)
Installation	Desktop/Rack mount
Certifications	FCC:47 CFR FCC Part15,SubpartB,Class A CE-FMC:EN 55032:2015 Class A;EN IEC 61000-3-2:2019;EN 61000-3-3:2013+A1:2019;EN