

# NVR5416-16P-4KS2E

Dahua NVR5416-16P-4KS2E WizSense 16 kanal PoE NVR; 4x10TB HDD; 12×1080p@30 fps; 14 kanal uz tanima; 16 kanal perimetr protection; 4 kanal ANPR; 16 kanal Stereo Analysis; 16 kanal Video Metadata; 16 kanal SMD Plus; Bandwidth 320 Mbps;

Model	NVR5416-16P-4KS2E
Brend	Dahua
Növ	NVR
Kanal sayı	16 kanal
PoE dəstəyi	PoE
Məqəpəxel	12 MP
Max HDD sayı	4 HDD
Max HDD həcmi	10 TB



## Specification

System	
Main Processor	Industrial embedded micro-processor
Operating System	Embedded Linux
Operation Interface	Web; local GUI
Perimeter Protection by Camera	
Performance	16 channels
AI Search	Search for pictures by channel, time and event type
Face Recognition by Camera	
Performance	14 channels
Face Attributes	6 attributes: Gender; age; glasses; expression; mouth mask; beard
AI Search	Search for pictures by channel, time and face attributes
SMD Plus by Camera	
Performance	16 channels
AI Search	Search by target classification (human, vehicle)
Video Metadata by Camera	
Performance	16 channels
Human Body	Top; top color; bottom; bottom color; hat; bag; gender; age; umbrella
Vehicle	Plate No.; type; color; vehicle type; logo; plate color; ornament; calling; seatbelt; region
Non-motor Vehicle	Type; color; number of passengers; helmet
AI Search	Supports searching for target video by metadata
ANPR by Camera	
Performance	4 channels
Stereo Analysis by Camera	
Performance	16 channels

AI Search	Search by target classification (fall detection; people approach detection; people No. exception detection; people staying detection; violence detection)
Video	
Access Channel	16
Network Bandwidth	320 Mbps for access, 320 Mbps for storage and 320 Mbps for forwarding
Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 1.3MP, 720p, D1, and more
Decoding Capability	16-channel@1080P (30 fps)
Video Output	HDMI1: 3840 × 2160; 1920 × 1080; 1280 × 1024; 1280 × 720 VGA1: 1920 × 1080; 1280 × 1024; 1280 × 720 HDMI2/VGA2: 1920 × 1080 VGA1/HDMI1 homologous output, VGA2/HDMI2 homologous output, and VGA1/HDMI1 and VGA2/HDMI2 supports heterogeneous output
Multi-screen Display	1st Screen: 1/4/8/9/16
	2nd screen: 1/4/8/9/16
Third Party Camera Access	Panasonic, Sony, Samsung, Axis, Pelco, Arecont, ONVIF, Canon and more
Compression	
Video	Smart H.265+; Smart H.264+; H.265; H.264; MJPEG
Audio	PCM; G.711A; G.711U; G.726
Network	
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4/IPv6; UPnP; SNMP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; PPPoE; DDNS; FTP; Alarm Server; IP Search (Supports Dahua IP camera, DVR, NVS, and more.); P2P
Mobile Phone Access	Android; iOS
Interoperability	ONVIF (profile T/S/G); CGI; SDK
Browser	Chrome; IE9 or later; Firefox
Record Playback	
Multi-channel Playback	1/4/9/16
Record Mode	Manual; schedule (general; MD; alarm; MD & alarm; intelligent; POS)
Storage Method	Local HDD and network
Backup	USB device
Playback Function	1. Play; pause; stop; fast forward; fast backward; rewind; play by frame 2. Full screen; backup (cut/file); partially enlarge; audio on/off
Storage	
Disk Group	Yes
Alarm	
General Alarm	Motion detection; privacy masking; video loss; local alarm; PIR alarm; IPC alarm
Anomaly Alarm	Camera offline; storage error; full storage; IP conflict; MAC conflict; login lock; network security anomaly
Intelligent Alarm	Perimeter protection; face detection; face recognition; SMD; video metadata (human; motor-vehicle; non-motor vehicle); ANPR; people counting; stereo analysis; crowd distribution; heat map
Alarm Linkage	Record; snapshot; IPC external alarm output; buzzer; log; preset; email
External Port	
Audio Input	1 channel, RCA connector
Audio Output	2 channels, RCA connector, which supports voice intercom output
HDD	4 SATA III ports, up to 10 TB for a single HDD. The maximum HDD capacity varies with environment temperature
Alarm Input	16 channels
Alarm Output	6 channels
eSATA	1 eSATA
RS-232	1 channel, used to debug and pass through serial data
RS-485	1 channel, used to control PTZ, and it supports multiple protocols
USB	1 front USB 2.0 port, 2 rear USB 3.0 ports
HDMI	2
VGA	2
Network	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet port
PoE	16 ports (IEEE802.3af/at) 1-8 ports support ePoE & EoC
General Parameter	

<b>Power Supply</b>	Single, 100V–240V AC, 50 Hz–60 Hz
<b>Power Consumption</b>	NVR: < 17.5W (without HDD) PoE: Max 25.5W for single port 150W total rated power, 80% control for protection
<b>Net Weight</b>	4.65 kg (10.3 lb) (without HDD)
<b>Gross Weight</b>	7 kg (15.4 lb) (without HDD)
<b>Product Dimensions</b>	440 mm × 412.2 mm × 76.0 mm (17.3" × 16.2" × 3.0")
<b>Package Dimensions</b>	522 mm × 492 mm × 200 mm (20.6" × 19.4" × 7.9")
<b>Operating Temperature</b>	-10°C to +55°C (+14°F to +131°F)
<b>Storage Temperature</b>	0°C to +40°C (+32°F to +104°F)
<b>Operating Humidity</b>	10%–93% (RH)
<b>Storage Humidity</b>	30%–85% (RH)
<b>Operating Altitude</b>	3,000 m (9,843 ft)
<b>Certifications</b>	CE: EN55032; EN55024; EN50130-4; EN60950-1 FCC: Part 15 Subpart B; ANSI C63.4-2014 UL: UL 60950-1